



### Main

Range of product	PacDrive 3
Product or component type	Motion controller

### Complementary

Product compatibility	LMC402
Number of axis	<= 16
Discrete input number	20 digital input conforming to IEC 61131-2 Type 1 4 interrupt input conforming to IEC 61131-2 Type 1 16 touch probe input conforming to IEC 61131-2 Type 1
Discrete input voltage	0...6 V 20...33 V
Discrete input voltage type	DC
Analogue input number	2
Analogue input type	Voltage analog input : - 10...10 V Current analog input : - 20...20 mA
Analogue input resolution	12 bits
Discrete input current	5 mA digital input 5 mA interrupt input 5 mA touch probe input
Input impedance	100000 Ohm analog input 500 Ohm
Anti bounce filtering	Configurable from 1 ms or 5 ms for digital input From 100 µs for touch probe input Configurable from 0.1 ms or 1 ms for interrupt input
Discrete output number	16 digital output 2 analog output
Discrete output current	250 mA for digital output
Leakage current	< 0.4 mA
Number of I/O expansion module	2
[Us] rated supply voltage	24 V DC
Power consumption	36 W
Memory type	NVRAM 256 kB RAM DDR3L 1 GB
Programming language	CFC (continuous function chart) FBD (function block diagram) IL (instruction list) LD (ladder) SFC (sequential function chart) ST (structured text)

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Integrated connection type	2 Ethernet port, connector RJ45 for protocol Sercos 1 CAN port, connector SUB-D 9 for protocol CANopen 1 USB port, connector USB type A 2 Ethernet port, connector RJ45 for protocol RT-Ethernet (real-time) 1 Ethernet port, connector RJ45 for protocol PacNet 1 port, connector SUB-D 9 for protocol Profibus DP 1 COM1 serial link, connector SUB-D 9 for protocol RS232 1 COM2 serial link, connector SUB-D 9 for protocol RS422/RS485 1 port, connector SUB-D 9 for master encoder 1 Ethernet port, connector RJ45 for protocol Ethernet 10/100/1000BASE-T, FTP/HTTP
Supply	Power supply 24 V DC, 1 A
Width	100 mm
Height	310 mm
Depth	243 mm
Product weight	3.5 kg

## Environment

Standards	EN/IEC 61131-2 UL 508C CSA C22.2 No 14 CSA C22.2 No 274
Product certifications	CE CSA CULus EAC
Ambient air temperature for operation	5...55 °C
Relative humidity	5...95 % without condensation
IP degree of protection	IP20 conforming to EN/IEC 60529
Pollution degree	2 conforming to IEC 61131-2
Vibration resistance	3.5 mm (f = 5...8.4 Hz) 10 m/s <sup>2</sup> (f = 8.4...150 Hz)
Shock resistance	150 m/s <sup>2</sup> (duration = 6 ms) conforming to EN/IEC 60721-3-3 operation

## Offer Sustainability

Sustainable offer status	Green Premium product
RoHS (date code: YYWW)	Compliant - since 1606 - <a href="#">Schneider Electric declaration of conformity</a>
REACH	Reference not containing SVHC above the threshold
Product environmental profile	Available
Product end of life instructions	Available