



Price* : 56.68 GBP



Main

Range	TeSys
Device short name	LUA
Product or component type	Limiter disconnecter

Complementary

Product compatibility	LUB LU2B
[Ith] conventional free air thermal current	32 A
Breaking capacity	70 kA at 690 V 130 kA
Mounting mode	Direct
[Ui] rated insulation voltage	690 V conforming to EN 60947-1 690 V conforming to IEC 60947-1
Irms rated making capacity	50 kA
Connections - terminals	Connector 1 x 1...10 mm ² flexible without cable end Connector 1 x 1...6 mm ² flexible with cable end Connector 2 x 1...6 mm ² flexible with cable end Connector 2 x 1...6 mm ² flexible without cable end Connector 1 x 1.5...10 mm ² solid Connector 2 x 1.5...6 mm ² solid
Tightening torque	1.9...2.5 N.m flat Ø 6 mm 1.9...2.5 N.m Philips No 2
Product weight	0.31 kg

Offer Sustainability

Sustainable offer status	Green Premium product
REACH free of SVHC	Yes
EU RoHS Directive	Compliant EU RoHS Declaration
Toxic heavy metal free	Yes

Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS declaration Pro-active China RoHS declaration (out of China RoHS legal scope)
Environmental Disclosure	Product Environmental Profile
Circularity Profile	No need of specific recycling operations
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

Contractual warranty

Warranty	18 months
----------	-----------