



Main

Device short name	OF
Product or component type	Auxiliary contact
Range compatibility	PowerPact B Compact NSXm
Signal contacts composition	1 NO/NC

Complementary

Auxiliary contacts type	Standard
Mounting mode	Clip-on
[I _{th}] conventional free air thermal current	5 A
[I _e] rated operational current	DC-12: 0.3 A at 250 V DC DC-14: 0.03 A at 250 V DC AC-12: 5 A at 24 V AC/DC 50/60 Hz AC-12: 5 A at 48 V AC/DC 50/60 Hz AC-12: 5 A at 110 V AC/DC 50/60 Hz AC-12: 5 A at 220...240 V AC 50/60 Hz AC-12: 5 A at 380...440 V AC 50/60 Hz AC-12: 5 A at 660...690 V AC 50/60 Hz AC-15: 5 A at 24 V AC/DC 50/60 Hz AC-15: 5 A at 48 V AC/DC 50/60 Hz AC-15: 4 A at 110 V AC/DC 50/60 Hz AC-15: 3 A at 220...240 V AC 50/60 Hz AC-15: 2.5 A at 380...440 V AC 50/60 Hz AC-15: 0.1 A at 660...690 V AC 50/60 Hz DC-12: 5 A at 24 V AC/DC 50/60 Hz DC-12: 2.5 A at 48 V AC/DC 50/60 Hz DC-12: 0.6 A at 110 V AC/DC 50/60 Hz DC-14: 2.5 A at 24 V AC/DC 50/60 Hz DC-14: 1.2 A at 48 V AC/DC 50/60 Hz DC-14: 0.35 A at 110 V AC/DC 50/60 Hz DC-14: 0.05 A at 250 V DC DC-14: 1 A at 24 V AC/DC 50/60 Hz DC-14: 0.2 A at 48 V AC/DC 50/60 Hz DC-14: 0.05 A at 110 V AC/DC 50/60 Hz
Minimum load	5 mA at 17 V DC
Auxiliary connection terminal	Pre-wired 0.8 mm ² (AWG 18) stranded copper
Wire stripping length	8 mm for front connection
Cable length	1 m

Offer Sustainability

REACH free of SVHC	Yes
EU RoHS Directive	Compliant EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS declaration Pro-active China RoHS declaration (out of China RoHS legal scope)
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

Contractual warranty

Warranty	18 months
----------	-----------