



Main

Range of product	NSX100...250
Product or component type	Control unit
Range compatibility	Compact NSX100 Compact NSX160 Compact NSX250
Device application	Generator
Poles description	4P
Protected poles description	3t + N/2 4t 3t
Neutral position	Left
Network type	AC
Network frequency	50/60 Hz
Trip unit name	Micrologic 2.2 G
Trip unit technology	Electronic
Trip unit protection functions	LSol
Protection type	L : for overload protection (long time) So : for short time short-circuit protection with fixed delay I : for instantaneous short-circuit protection
Trip unit rating	100 A at 40 °C

Complementary

Mounting mode	Fixed
[Ue] rated operational voltage	690 V AC 50/60 Hz
Neutral protection setting	0.5 x Ir (3t + N/2) 1 x Ir (4t) No protection (3t)
Long time pick-up adjustment type Ir	Adjustable 9 settings

[Ir] long time pick-up adjustment range	0.9...1 x I _o
Long time delay adjustment type	Fixed
[Tr] long-time delay adjustment range	15 s at 1.5 x I _r 0.35 s at 7.2 x I _r 0.5 s at 6 x I _r
Thermal memory	20 minutes before and after tripping
Short-time pick-up adjustment type I _{sd}	Adjustable
[I _{sd}] short-time pick-up adjustment range	1.5...9 x I _r
Short-time delay adjustment type	Fixed
[T _{sd}] short-time delay adjustment range	0.14 s
Instantaneous pick-up adjustment type I _i	Fixed
[I _i] instantaneous pick-up adjustment range	1500 A

Environment

Standards	EN/IEC 60947-2 UL 508
Product certifications	Marine EAC CCC
Ambient air temperature for operation	-25...70 °C
Ambient air temperature for storage	-50...85 °C

Offer Sustainability

Sustainable offer status	Green Premium product
EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End of Life Information

Contractual warranty

Warranty	18 months
----------	-----------