



Main

Range of product	NSX100...250
Product or component type	Control unit
Range compatibility	Compact NSX100 Compact NSX160 Compact NSX250
Device application	Distribution
Poles description	4P
Protected poles description	3t + 1.6 N 4t 3t + N/2 3t
Neutral position	Left
Network type	AC
Network frequency	50/60 Hz
Trip unit name	Micrologic 5.2 A
Trip unit technology	Electronic
Trip unit protection functions	LSI
Protection type	L : for overload protection (long time) S : for short time short-circuit protection I : for instantaneous short-circuit protection
Trip unit rating	100 A at 40 °C

Complementary

Mounting mode	Fixed
[Ue] rated operational voltage	690 V AC 50/60 Hz
Neutral protection setting	0.5 x Ir (3t + N/2) 1 x Ir (4t) 1.6 x Ir (3t + OSN) No protection (3t)

Long time pick-up adjustment type I_r	Adjustable 9 settings
$[I_r]$ long time pick-up adjustment range	40...100 A
Long time delay adjustment type	Adjustable
$[T_r]$ long-time delay adjustment range	15...400 s at 1.5 x I_r 0.35...11 s at 7.2 x I_r 0.5...16 s at 6 x I_r
Thermal memory	20 minutes before and after tripping
Short-time pick-up adjustment type I_{sd}	Adjustable 9 settings
$[I_{sd}]$ short-time pick-up adjustment range	1.5...10 x I_r
Short-time delay adjustment type	Adjustable
$[T_{sd}]$ short-time delay adjustment range	0...0.4 s $I^2t=off$ 0.1...0.4 s $I^2t=on$
Instantaneous pick-up adjustment type I_i	Adjustable
$[I_i]$ instantaneous pick-up adjustment range	1.5...15 x I_n
Zone selective interlocking ZSI	With
Communication of data	Protection and alarm settings Maximeters/minimeters Instantaneous and demand values Demand current and power Maintenance indicators Power quality Energy metering Time-stamped histories and event tables
Display type	LCD display
Type of measurement	Ammeter
Electrical data recording	Maintenance indicators

Environment

Standards	EN/IEC 60947-2 UL 508
Product certifications	CCC Marine EAC
Ambient air temperature for operation	-25...70 °C
Ambient air temperature for storage	-40...85 °C

Offer Sustainability

Sustainable offer status	Green Premium product
EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End of Life Information

Contractual warranty

Warranty	18 months
----------	-----------