Product datasheet Characteristics

LV429325

voltage presence indicator, Compact NSX 100/160/250, 3 or 4 poles



Main	
Range of product	

Range of product	NSX100250 INV100250 INS250		
Range	Compact		
Product or component type	Voltage presence indicator		
Device application	Monitoring		
Range compatibility	Compact INS circuit breaker Compact INV circuit breaker Compact NSX circuit breaker		
Poles description	3P 4P		
Network type	AC		
[In] rated current	250 A		

Complementary

[Ue] rated operational voltage	220550 V
Network frequency	50/60 Hz

Environment

IP degree of protection	IP40 conforming to IEC 60529
IK degree of protection	IK04 conforming to IEC 62262

Offer Sustainability

Range of product	NSX100250	
	INV100250	
	INS250	
Range	Compact	
Product or component type	Voltage presence indicator	
Device application	Monitoring	
Range compatibility	Compact INS circuit breaker	
	Compact INV circuit breaker Compact NSX circuit breaker	
Poles description	3P	
Toles description	4P	
Network type	AC	
[In] rated current	250 A	
Complementary		
[Ue] rated operational voltage	220550 V	
Network frequency	50/60 Hz	
Environment		
IP degree of protection	IP40 conforming to IEC 60529	
IK degree of protection	IK04 conforming to IEC 62262	
Offer Sustainability		
EU RoHS Directive	Compliant	
	EU RoHS Declaration	
Mercury free	Yes	
RoHS exemption information	Yes	
China RoHS Regulation	China RoHS declaration	
	Product out of China RoHS scope. Substance declaration for your information	
Contractual warranty		
Warranty	18 months	

Contractual warranty

Warranty	10 months	ē
vvarrantv	TO MONUS	
		·-