# **Product datasheet** Characteristics

## LV429408

MN undervoltage release, Compact NSX, PowerPact Multistandard, EasyPact CVS, rated voltage 380 to 415 VAC 50/60 Hz, 440 to 480 VAC 60 Hz





### Main

Device short name	MN
Product or component type	Voltage release
Device application	Control
Range compatibility	Compact NSX EasyPact CVS PowerPact Multistandard
Voltage release type	Undervoltage release
[Uc] control circuit voltage	380415 V AC 50 Hz 440480 V AC 60 Hz

### Complementary

Threshold tripping voltage	0.350.7 x Un opening 0.85 x Un closing	n total
Supply holding power	5 VA	
Supply inrush power	10 VA	e or
Mounting mode	Fixed	119
Response time	50 ms	
Auxiliary connection terminal	Screw terminal01.5 mm²	9 9 8

#### Offer Sustainability

		U
Sustainable offer status	Green Premium product	
REACh Regulation	REACh Declaration	- ctron
EU RoHS Directive	Compliant EU RoHS Declaration	ši SCC CL
Mercury free	Yes	Ė
RoHS exemption information	Yes	.E

China RoHS Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information	
Environmental Disclosure	Product Environmental Profile	
Circularity Profile	No need of specific recycling operations	
Contractual warranty		
Warranty	18 months	