



Main

Range of product	NSX100...250
Product or component type	Trip unit
Range compatibility	Compact NSX250
Device application	Motor
Poles description	4P
Protected poles description	3t
Neutral position	Left
Network type	AC
Network frequency	50/60 Hz
Trip unit name	MA
Trip unit technology	Magnetic
Trip unit protection functions	I
Protection type	I : for short-circuit protection (magnetic)
Trip unit rating	220 A at 65 °C

Complementary

Mounting mode	Fixed
[Ue] rated operational voltage	690 V AC 50/60 Hz
Neutral protection setting	No protection
Instantaneous pick-up adjustment type Ii	Adjustable
[Ii] instantaneous pick-up adjustment range	9...14 x In

Environment

Standards	EN/IEC 60947-2 UL 508
Product certifications	Marine

CCC
EAC

Ambient air temperature for operation	-25...70 °C
Ambient air temperature for storage	-50...85 °C

Offer Sustainability

Sustainable offer status	Green Premium product
EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information
Environmental Disclosure	Product Environmental Profile
Circularity Profile	No need of specific recycling operations
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

Contractual warranty

Warranty	18 months
----------	-----------