



### Main

Device short name	Motor mechanism module with SDE adaptor
Product or component type	Motor mechanism
Device application	Automatic spring charging
Range compatibility	Compact NSX circuit breaker Compact NSX DC circuit breaker circuit breaker
Product compatibility	PowerPact J-Frame PowerPact H-Frame
[In] rated current	250 A
[Uc] control circuit voltage	110...130 V AC 50/60 Hz

### Complementary

Control type	Standard
Control signal type	Impulse Maintained
Mounting mode	Fixed
Response time	< 600 ms (opening) < 80 ms (closing)
Maximum operating frequency	4 per minute
Maximum power consumption in VA	500 VA closing 500 VA opening
Provided equipment	SDE adaptor
Locking options description	Padlocking in OFF position 1 to 3 padlocks Ø 5 to Ø 8

### Offer Sustainability

Sustainable offer status	Green Premium product
EU RoHS Directive	Compliant

[EU RoHS Declaration](#)

Mercury free	Yes
RoHS exemption information	<a href="#">Yes</a>
China RoHS Regulation	<a href="#">China RoHS declaration</a> Product out of China RoHS scope. Substance declaration for your information
Environmental Disclosure	<a href="#">Product Environmental Profile</a>
Circularity Profile	<a href="#">End of Life Information</a>

**Contractual warranty**

Warranty	18 months
----------	-----------