




Main

Range of product	NSX400...630
Product or component type	Control unit
Range compatibility	Compact NSX400 Compact NSX630
Device application	Distribution Generator
Poles description	4P
Protected poles description	3t + N/2 3t 4t 3t + 1.6 N
Neutral position	Left
Network type	AC
Network frequency	50/60 Hz
Trip unit name	Micrologic 6.3 A
Trip unit technology	Electronic
Trip unit protection functions	LSIG
Protection type	L : for overload protection (long time) S : for short time short-circuit protection I : for instantaneous short-circuit protection G : for ground fault protection
Trip unit rating	400 A at 40 °C

Complementary

Mounting mode	Fixed
[Ue] rated operational voltage	690 V AC 50/60 Hz
Neutral protection setting	0.5 x Ir (3t + N/2) 1 x Ir (4t) 1.6 x Ir (3t + OSN) No protection (3t)
Long time pick-up adjustment type Ir	Adjustable
[Ir] long time pick-up adjustment range	160...400 A
Long time delay adjustment type	Adjustable

[Tr] long-time delay adjustment range	15...400 s at 1.5 x Ir 0.35...11 s at 7.2 x Ir 0.5...16 s at 6 x Ir
Thermal memory	20 minutes before and after tripping
Short-time pick-up adjustment type Isd	Adjustable
[Isd] short-time pick-up adjustment range	1.5...10 x Ir
Short-time delay adjustment type	Adjustable
[Tsd] short-time delay adjustment range	0...0.4 s I ² t=off 0.1...0.4 s I ² t=on
Instantaneous pick-up adjustment type li	Adjustable
[li] instantaneous pick-up adjustment range	1.5...11 x In Compact NSX630 1.5...12 x In Compact NSX400
Ground-fault pick-up adjustment type	Adjustable
[Ig] ground-fault pick-up adjustment range	0.2...1 x In
Ground-fault time delay adjustment type -tg	Adjustable
Zone selective interlocking ZSI	With
Communication of data	Time-stamped histories and event tables Maximeters/minimeters Demand current and power Maintenance indicators Power quality Instantaneous and demand values Energy metering Protection and alarm settings
Display type	LCD display
Type of measurement	Ammeter
Electrical data recording	Maintenance indicators

Environment

Standards	UL 508 EN/IEC 60947-2
Product certifications	Marine EAC CCC
IP degree of protection	IP40 conforming to IEC 60529
Pollution degree	3 conforming to IEC 60947-1
Ambient air temperature for operation	-25...70 °C
Ambient air temperature for storage	-40...85 °C

Offer Sustainability

EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information

Contractual warranty

Warranty	18 months
----------	-----------