



Main

| | |
|----------------------------------------------------|-----------------------------------|
| Range of product | NSX400...630 |
| Range | Compact |
| Product or component type | Vigi add-on |
| Device application | Wiring |
| Range compatibility | Compact NSX circuit breaker |
| Poles description | 3P |
| [In] rated current | 400 A 630 A |
| Earth-leakage add-on module name | MB |
| Earth-leakage protection class | Class A |
| Residual earth-leakage sensitivity adjustment type | Adjustable 5 settings |
| [IΔn] residual earth-leakage sensitive adjustment | 0.3...30 A |
| Residual earth-leakage time delay adjustment type | Adjustable 4 settings |
| [Δt] residual earth-leakage time delay adjustment | 60 ms 150 ms 0 ms 310 ms |

Complementary

| | |
|--------------------------------|---------------------------------------------------|
| Network type | AC |
| Network frequency | 50/60 Hz |
| [Ue] rated operational voltage | 440...550 V AC 50/60 Hz conforming to IEC 60947-2 |
| Earth-leakage protection | With |
| Maximum breaking time | 800 ms |
| Oversvoltage category | Class II |

Environment

| | |
|-----------------------------------|-------------|
| Electrical shock protection class | Class II |
| Standards | IEC 60947-2 |

Offer Sustainability

| | |
|----------------------------|-----------------------------------------------------------------------------------------------------------------------|
| EU RoHS Directive | Compliant EU RoHS Declaration |
| Mercury free | Yes |
| RoHS exemption information | Yes |
| China RoHS Regulation | China RoHS declaration Product out of China RoHS scope. Substance declaration for your information |

Contractual warranty

| | |
|----------|-----------|
| Warranty | 18 months |
|----------|-----------|