



## Main

|                                        |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            |
|----------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Range                                  | Compact                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    |
| Product name                           | Compact NSX                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                |
| Product or component type              | Circuit breaker                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            |
| Device short name                      | Compact NSX400H                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            |
| Device application                     | Distribution                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                               |
| Poles description                      | 3P                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         |
| Protected poles description            | 3t                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         |
| Network type                           | AC                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         |
| Network frequency                      | 50/60 Hz                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   |
| [In] rated current                     | 400 A at 40 °C                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             |
| [Ui] rated insulation voltage          | 800 V AC 50/60 Hz                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                          |
| [Uimp] rated impulse withstand voltage | 8 kV                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       |
| [Ue] rated operational voltage         | 690 V AC 50/60 Hz                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                          |
| Breaking capacity code                 | H 70 kA 415 V AC                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                           |
| Breaking capacity                      | 85 kA at 240 V AC 50/60 Hz conforming to UL 508<br>65 kA at 480 V AC 50/60 Hz conforming to UL 508<br>100 kA Icu at 220/240 V AC 50/60 Hz conforming to IEC 60947-2<br>35 kA Icu at 525 V AC 50/60 Hz conforming to IEC 60947-2<br>50 kA Icu at 500 V AC 50/60 Hz conforming to IEC 60947-2<br>65 kA Icu at 440 V AC 50/60 Hz conforming to IEC 60947-2<br>70 kA Icu at 380/415 V AC 50/60 Hz conforming to IEC 60947-2<br>20 kA at 600 V AC 50/60 Hz conforming to UL 508<br>20 kA Icu at 660/690 V AC 50/60 Hz conforming to IEC 60947-2 |
| [Ics] rated service breaking capacity  | 11 kA at 525 V AC 50/60 Hz conforming to IEC 60947-2<br>10 kA at 660/690 V AC 50/60 Hz conforming to IEC 60947-2<br>100 kA at 220/240 V AC 50/60 Hz conforming to IEC 60947-2<br>50 kA at 500 V AC 50/60 Hz conforming to IEC 60947-2<br>65 kA at 440 V AC 50/60 Hz conforming to IEC 60947-2<br>70 kA at 380/415 V AC 50/60 Hz conforming to IEC 60947-2                                                                                                                                                                                  |
| Suitability for isolation              | Yes conforming to EN 60947-2<br>Yes conforming to IEC 60947-2                                                                                                                                                                                                                                                                                                                                                                                                                                                                              |
| Utilisation category                   | Category A                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 |

|                                |                             |
|--------------------------------|-----------------------------|
| Trip unit name                 | Micrologic 5.3 A            |
| Trip unit technology           | Electronic                  |
| Trip unit protection functions | LSI                         |
| Pollution degree               | 3 conforming to IEC 60664-1 |

## Complementary

|                                           |                                                                                                                                                                                                                                |
|-------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Control type                              | Toggle                                                                                                                                                                                                                         |
| Mounting mode                             | Fixed                                                                                                                                                                                                                          |
| Mounting support                          | Backplate                                                                                                                                                                                                                      |
| Upside connection                         | Front                                                                                                                                                                                                                          |
| Downside connection                       | Front                                                                                                                                                                                                                          |
| Auxiliary contact composition             | Without                                                                                                                                                                                                                        |
| Mechanical durability                     | 15000 cycles                                                                                                                                                                                                                   |
| Electrical durability                     | 12000 cycles 440 V In/2 conforming to IEC 60947-2<br>3000 cycles 690 V In conforming to IEC 60947-2<br>6000 cycles 440 V In conforming to IEC 60947-2<br>6000 cycles 690 V In/2 conforming to IEC 60947-2                      |
| Connection pitch                          | 45 mm                                                                                                                                                                                                                          |
| Local signalling                          | LED 90 % Ir<br>LED 105 % Ir<br>LED ready                                                                                                                                                                                       |
| Protection type                           | L : for overload protection (long time)<br>S : for short time short-circuit protection<br>I : for instantaneous short-circuit protection                                                                                       |
| Trip unit rating                          | 400 A at 40 °C                                                                                                                                                                                                                 |
| Long time pick-up adjustment type Ir      | Adjustable                                                                                                                                                                                                                     |
| Long time pick-up adjustment range        | 100...400 A                                                                                                                                                                                                                    |
| Long time delay adjustment type           | Adjustable                                                                                                                                                                                                                     |
| [Tr] long-time delay adjustment range     | 15...400 s at 1.5 x Ir<br>0.35...11 s at 7.2 x Ir<br>0.5...16 s at 6 x Ir                                                                                                                                                      |
| Thermal memory                            | 20 minutes before and after tripping                                                                                                                                                                                           |
| Short-time pick-up adjustment type Isd    | Adjustable                                                                                                                                                                                                                     |
| [Isd] short-time pick-up adjustment range | 1.5...10 x Ir                                                                                                                                                                                                                  |
| Short-time delay adjustment type          | Adjustable                                                                                                                                                                                                                     |
| [Tsd] short-time delay adjustment range   | 0...0.4 s                                                                                                                                                                                                                      |
| Instantaneous pick-up adjustment type Ii  | Adjustable                                                                                                                                                                                                                     |
| Instantaneous pick-up adjustment range    | 1.5...12 x In                                                                                                                                                                                                                  |
| Zone selective interlocking ZSI           | With                                                                                                                                                                                                                           |
| Communication of data                     | Maximeters/minimeters<br>Time-stamped histories and event tables<br>Power quality<br>Maintenance indicators<br>Protection and alarm settings<br>Instantaneous and demand values<br>Demand current and power<br>Energy metering |
| Display type                              | LCD display                                                                                                                                                                                                                    |
| Type of measurement                       | Ammeter                                                                                                                                                                                                                        |
| Electrical data recording                 | Maintenance indicators                                                                                                                                                                                                         |
| Height                                    | 255 mm                                                                                                                                                                                                                         |
| Width                                     | 140 mm                                                                                                                                                                                                                         |
| Depth                                     | 110 mm                                                                                                                                                                                                                         |
| Product weight                            | 6.05 kg                                                                                                                                                                                                                        |

|                    |        |
|--------------------|--------|
| Compatibility code | NSX400 |
|--------------------|--------|

## Environment

|                                       |                              |
|---------------------------------------|------------------------------|
| Overvoltage category                  | Class II                     |
| Electrical shock protection class     | Class II                     |
| Standards                             | EN/IEC 60947<br>UL 508       |
| Product certifications                | Marine<br>EAC<br>CCC         |
| IP degree of protection               | IP40 conforming to IEC 60529 |
| IK degree of protection               | IK07 conforming to IEC 62262 |
| Ambient air temperature for operation | -35...70 °C                  |
| Ambient air temperature for storage   | -55...85 °C                  |

## Offer Sustainability

|                            |                                                                                                                       |
|----------------------------|-----------------------------------------------------------------------------------------------------------------------|
| Sustainable offer status   | Green Premium product                                                                                                 |
| EU RoHS Directive          | Compliant<br><a href="#">EU RoHS Declaration</a>                                                                      |
| Mercury free               | Yes                                                                                                                   |
| RoHS exemption information | <a href="#">Yes</a>                                                                                                   |
| China RoHS Regulation      | <a href="#">China RoHS declaration</a><br>Product out of China RoHS scope. Substance declaration for your information |
| Environmental Disclosure   | <a href="#">Product Environmental Profile</a>                                                                         |
| Circularity Profile        | <a href="#">End of Life Information</a>                                                                               |

## Contractual warranty

|          |           |
|----------|-----------|
| Warranty | 18 months |
|----------|-----------|