Product datasheet Characteristics

LV432858

current transformer module, Compact NSX 630, 630 A rating, 4 poles



Range of product	NSX400630				
9 - 1 - 1 - 1 - 1 - 1 - 1 - 1 - 1 - 1 -	INV320630				
	INS320630				
Range	Compact				
Device short name	Current transformer module				
Product or component type	Current transformer				
Device application	Control				
Range compatibility	Compact INS circuit breaker				
	Compact INV circuit breaker				
	Compact NSX circuit breaker				
Poles description	4P				
[In] rated current	600 A				
Complementary					
Current transformer ratio	600/5 A				
Current transferrior ratio					
Auxiliary connection terminal	Cable connector 2.5 mm²				
Auxiliary connection terminal Environment					
Auxiliary connection terminal Environment Electrical shock protection class	Class II				
Auxiliary connection terminal Environment Electrical shock protection class IP degree of protection	Class II IP40 conforming to IEC 60529				
Auxiliary connection terminal Environment Electrical shock protection class IP degree of protection	Class II				
Auxiliary connection terminal Environment Electrical shock protection class IP degree of protection IK degree of protection	Class II IP40 conforming to IEC 60529				
Auxiliary connection terminal Environment Electrical shock protection class IP degree of protection IK degree of protection	Class II IP40 conforming to IEC 60529				
Environment Electrical shock protection class IP degree of protection IK degree of protection Offer Sustainability	Class II IP40 conforming to IEC 60529 IK04 conforming to IEC 62262 Compliant				
Environment Electrical shock protection class IP degree of protection IK degree of protection Offer Sustainability EU RoHS Directive	Class II IP40 conforming to IEC 60529 IK04 conforming to IEC 62262 Compliant EU RoHS Declaration				
Auxiliary connection terminal Environment Electrical shock protection class IP degree of protection IK degree of protection Offer Sustainability EU RoHS Directive Mercury free	Class II IP40 conforming to IEC 60529 IK04 conforming to IEC 62262 Compliant EU RoHS Declaration Yes				
Environment Electrical shock protection class IP degree of protection IK degree of protection Offer Sustainability EU RoHS Directive Mercury free RoHS exemption information	Class II IP40 conforming to IEC 60529 IK04 conforming to IEC 62262 Compliant EU RoHS Declaration				
	Class II IP40 conforming to IEC 60529 IK04 conforming to IEC 62262 Compliant EU RoHS Declaration Yes Yes China RoHS declaration				
Environment Electrical shock protection class IP degree of protection IK degree of protection Offer Sustainability EU RoHS Directive Mercury free RoHS exemption information	Class II IP40 conforming to IEC 60529 IK04 conforming to IEC 62262 Compliant EU RoHS Declaration Yes Yes				
Environment Electrical shock protection class IP degree of protection IK degree of protection Offer Sustainability EU RoHS Directive Mercury free RoHS exemption information China RoHS Regulation	Class II IP40 conforming to IEC 60529 IK04 conforming to IEC 62262 Compliant EU RoHS Declaration Yes Yes China RoHS declaration				
Environment Electrical shock protection class IP degree of protection IK degree of protection Offer Sustainability EU RoHS Directive Mercury free RoHS exemption information	Class II IP40 conforming to IEC 60529 IK04 conforming to IEC 62262 Compliant EU RoHS Declaration Yes Yes China RoHS declaration				

Complementary

Current transformer ratio	600/5 A
Auxiliary connection terminal	Cable connector 2.5 mm²

Environment

Electrical shock protection class	Class II	
IP degree of protection	IP40 conforming to IEC 60529	
IK degree of protection	IK04 conforming to IEC 62262	

Offer Sustainability

o nor odotamasmity		
EU RoHS Directive	Compliant EU RoHS Declaration	
Mercury free	Yes	:
RoHS exemption information	Yes	
China RoHS Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information	

Contractual warranty

Warranty	18 months		