Product datasheet Characteristics

LV432861

CT module and voltage output - 600 A - 3 poles for NSX400...630



1	VI	а	Ш	٦
	-			-

Main		
Range of product	NSX400630	
Range	Compact	
Device short name	CT module and voltage output	
Product or component type	Current transformer	
Device application	Control	
Range compatibility	Compact NSX circuit breaker	
Poles description	3P	
Network type	AC	
[In] rated current	600 A 2 VA	
Complementary	500.14	
[Ue] rated operational voltage	530 V	
Network frequency	50/60 Hz	
Current transformer ratio	600/5 A	
Auxiliary connection terminal	Cable connector 2.5 mm²	
	Cable connector 2.5 mm²	
Auxiliary connection terminal	Cable connector 2.5 mm²	
	Cable connector 2.5 mm² Class II	
Auxiliary connection terminal Environment		
Auxiliary connection terminal Environment Electrical shock protection class	Class II	
Auxiliary connection terminal Environment Electrical shock protection class IP degree of protection	Class II IP40 conforming to IEC 60529	
Auxiliary connection terminal Environment Electrical shock protection class IP degree of protection IK degree of protection	Class II IP40 conforming to IEC 60529	
Auxiliary connection terminal Environment Electrical shock protection class IP degree of protection IK degree of protection Offer Sustainability	Class II IP40 conforming to IEC 60529	
Environment Electrical shock protection class IP degree of protection IK degree of protection Offer Sustainability EU RoHS Directive	Class II IP40 conforming to IEC 60529 IK04 conforming to IEC 62262 Compliant	
Auxiliary connection terminal Environment Electrical shock protection class IP degree of protection	Class II IP40 conforming to IEC 60529 IK04 conforming to IEC 62262 Compliant EU RoHS Declaration	
Auxiliary connection terminal Environment Electrical shock protection class IP degree of protection IK degree of protection Offer Sustainability EU RoHS Directive Mercury free	Class II IP40 conforming to IEC 60529 IK04 conforming to IEC 62262 Compliant EU RoHS Declaration Yes	
Environment Electrical shock protection class IP degree of protection IK degree of protection Offer Sustainability EU RoHS Directive Mercury free RoHS exemption information	Class II IP40 conforming to IEC 60529 IK04 conforming to IEC 62262 Compliant EU RoHS Declaration Yes Yes China RoHS declaration	
Environment Electrical shock protection class IP degree of protection IK degree of protection Offer Sustainability EU RoHS Directive Mercury free RoHS exemption information	Class II IP40 conforming to IEC 60529 IK04 conforming to IEC 62262 Compliant EU RoHS Declaration Yes Yes China RoHS declaration	

Complementary

[Ue] rated operational voltage	530 V
Network frequency	50/60 Hz
Current transformer ratio	600/5 A
Auxiliary connection terminal	Cable connector 2.5 mm²

Environment

Electrical shock protection class	Class II	.:
IP degree of protection	IP40 conforming to IEC 60529	
IK degree of protection	IK04 conforming to IEC 62262	

Offer Sustainability

EU RoHS Directive	Compliant EU RoHS Declaration	
Mercury free	Yes	
RoHS exemption information	Yes	
China RoHS Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information	

Contractual warranty

Warrantv	18 months