



Price* : 223.20 GBP



Main

Range	TeSys
Product or component type	Contacteur coil
Device short name	LX4FK
Range compatibility	TeSys F LC1F contacteur
Product compatibility	LC1F500
Control circuit type	DC low consumption
[Uc] control circuit voltage	340 V DC
Average resistance	89.6 Ohm inrush at 20 °C 21750 Ohm holding at 20 °C
Operating time	45...60 ms opening 50...60 ms closing

Complementary

Coil technology	Without built-in suppressor module
Control circuit voltage limits	Drop-out: 0.2...0.35 Uc (at 55 °C) Operational: 0.85...1.1 Uc (at 55 °C)

Environment

Ambient air temperature for operation	-5...55 °C
---------------------------------------	------------

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes

RoHS exemption information	Yes
China RoHS Regulation	China RoHS declaration
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End of Life Information

Contractual warranty

Warranty	18 months
----------	-----------