

PLUG-IN RELAY COMPLETE UNIT AC 230V,
4 CO CONTACT LED MODULE RED SOCKET W. LOGIC
ISOLATION SCREW TERMINAL 3.5 MM PINNING

General technical details:

Supply voltage frequency / for auxiliary and control current circuit / rated value

- minimum
- maximum

Hz 50
Hz 60

Type of voltage

AC

Control supply voltage

- at 50 Hz / at AC / rated value
 - minimum
 - maximum
- at 60 Hz / at AC / rated value
 - minimum
 - maximum

V 230
V 230
V 230
V 230

Number of NC contacts

- for auxiliary contacts

0

Number of NO contacts

- for auxiliary contacts

0

Number of changeover contacts

- for auxiliary contacts

4

Operating current / of the auxiliary contacts

- at DC-13
 - at 24 V
- at AC-15
 - at 230 V

A 6
A 4

Design of the switching function

- guided

changeover switch
No

Switching behaviour

monostable

Mechanical design:

Design of the electrical connection

screw-type terminals

Design of the relay operating mechanism

poled

Product component / jumper socket

Yes

Width

mm 28

Height	mm	79
Depth	mm	77

Certificates/approvals:

other

[Declaration of
Conformity](#)

Further information:

Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/industrial-controls/catalogs>

Industry Mall (Online ordering system)

<http://www.siemens.com/industrial-controls/mall>

CAX-Online-Generator

<http://www.siemens.com/cax>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<http://support.automation.siemens.com/WW/view/en/LZS:PT5B5T30/all>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=LZS:PT5B5T30

last change:

Jun 16, 2014