

LED MODULE, RED FOR PLUG-IN RELAY,
SERIES PT AND RT, FOR 230V AC,
W. OUT FREE-WHEELING DIODE

General technical details:

Supply voltage frequency / for auxiliary and control current circuit / rated value

- minimum
- maximum

Hz
Hz

50
60

Type of voltage

AC/DC

Control supply voltage

- at 50 Hz / at AC / rated value
 - minimum
 - maximum
- at 60 Hz / at AC / rated value
 - minimum
 - maximum
- for DC / rated value
 - minimum
 - maximum

V
V
V
V
V
V

110
230
110
230
110
230

Number of NC contacts

- for auxiliary contacts

0

Number of NO contacts

- for auxiliary contacts

0

Number of changeover contacts

- for auxiliary contacts

0

Design of the switching function

- guided

changeover switch
No

Switching behaviour

monostable

Mechanical design:

Design of the electrical connection

screw-type terminals

Design of the relay operating mechanism

poled

Product component / jumper socket

No

Width

mm

15.5

Certificates/approvals:

**General Product
Approval**

other



[Declaration of
Conformity](#)

Further information:

Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/industrial-controls/catalogs>

Industry Mall (Online ordering system)

<http://www.siemens.com/industrial-controls/mall>

CAX-Online-Generator

<http://www.siemens.com/cax>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<http://support.automation.siemens.com/WW/view/en/LZS:PTML0730/all>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=LZS:PTML0730

last change:

Jun 16, 2014