



PLUG-IN RELAY COMPACT UNIT DC 24V,
1 CO CONTACT LED MODULE RED STANDARD PLUG-IN
SOCKET 5 MM PINNING

General technical details:		
Type of voltage		DC
Control supply voltage		
• for DC / rated value		
• minimum	V	24
• maximum	V	24
Number of NC contacts		
• for auxiliary contacts		0
Number of NO contacts		
• for auxiliary contacts		0
Number of changeover contacts		
• for auxiliary contacts		1
Operating current / of the auxiliary contacts		
• at AC-15		
• at 230 V	A	3
Design of the switching function		changeover switch
• guided		No
Switching behaviour		monostable
Mechanical design:		
Design of the electrical connection		screw-type terminals

Design of the relay operating mechanism		poled
Product component / jumper socket		Yes
Width	mm	15.5
Height	mm	71
Depth	mm	78

Certificates/approvals:

other

[Declaration of
Conformity](#)

Further information:

Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/industrial-controls/catalogs>

Industry Mall (Online ordering system)

<http://www.siemens.com/industrial-controls/mall>

CAX-Online-Generator


<http://www.siemens.com/cax>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<http://support.automation.siemens.com/WW/view/en/LZS:RT3A4L24/all>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=LZS:RT3A4L24



last change:

Jun 16, 2014