



Main

Range of product	Multi 9
Product or component type	Shunt trip release
Device short name	MX
[Uc] control circuit voltage	12...24 V AC 50/60 Hz 12...24 V DC
9 mm pitches	2

Complementary

Range compatibility	Multi 9 C60 C60BP Multi 9 C60 C60BPR Multi 9 C60 C60SP Multi 9 GFP GFP Multi 9 C60H-DC C60H-DC
Local signalling	Action indicator
Mounting mode	Fixed
Mounting support	DIN rail
Height	82.5 mm
Width	18 mm
Depth	68 mm
Net weight	0.06 kg
Connections - terminals	Clamp terminal (bottom) - 1 cable(s) 2.5 mm ² (AWG 14) - rigid Clamp terminal (bottom) - 2 cable(s) 1.5 mm ² (AWG 16) - rigid
Wire stripping length	9 mm for bottom connection
Tightening torque	1 N.m bottom

Environment

Standards	EN/IEC 60947-1
Product certifications	UR PCT

	CSA UL
Pollution degree	3
Tropicalisation	2 conforming to EN/IEC 60947-1
Relative humidity	95 % at 55 °C
Ambient air temperature for operation	-25...50 °C
Ambient air temperature for storage	-40...85 °C

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Compliant EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS declaration Pro-active China RoHS declaration (out of China RoHS legal scope)
Environmental Disclosure	Product Environmental Profile
Circularity Profile	No need of specific recycling operations

Contractual warranty

Warranty	18 months
----------	-----------