



## Main

|                           |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      |
|---------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Range                     | Multi 9                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              |
| Product name              | Multi 9 C60                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                          |
| Product or component type | Miniature circuit-breaker                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            |
| Device short name         | C60BP                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                |
| Device application        | Distribution                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         |
| Poles description         | 3P                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   |
| Number of protected poles | 3                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    |
| [In] rated current        | 4 A at 25 °C conforming to EN/IEC 60947-2                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            |
| Network type              | AC                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   |
| Trip unit technology      | Thermal-magnetic                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     |
| Curve code                | C                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    |
| Breaking capacity         | 6 kA Icu at 440 V AC conforming to EN/IEC 60947-2<br>10 kA Icu at 415 V AC conforming to EN/IEC 60947-2<br>20 kA Icu at 240 V AC conforming to EN/IEC 60947-2<br>6 kA Icu at 440 V AC conforming to GB 14048.2<br>10 kA Icu at 415 V AC conforming to GB 14048.2<br>20 kA Icu at 240 V AC conforming to GB 14048.2<br>14 kA AIR at 240 V AC conforming to UL 489<br>10 kA AIR at 480Y/277 V AC conforming to UL 489<br>14 kA AIR at 240 V AC conforming to CSA C22.2 No 5<br>10 kA AIR at 480Y/277 V AC conforming to CSA C22.2 No 5 |
| Suitability for isolation | Yes conforming to EN/IEC 60947-2                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     |
| Standards                 | EN/IEC 60947-2<br>GB 14048.2<br>UL 489<br>CSA C22.2 No 5                                                                                                                                                                                                                                                                                                                                                                                                                                                                             |
| Product certifications    | IEC<br>CCC<br>CSA<br>UL                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              |

## Complementary

|                                        |                                                                                                                                                                                                                                                                                                                          |
|----------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| [Ue] rated operational voltage         | 240 V AC 50/60 Hz<br>415 V AC 50/60 Hz<br>440 V AC 50/60 Hz                                                                                                                                                                                                                                                              |
| Magnetic tripping limit                | 8.5 x I <sub>n</sub> +/- 20 % AC                                                                                                                                                                                                                                                                                         |
| [Ics] rated service breaking capacity  | 4.5 kA 75 % conforming to EN/IEC 60947-2 - 440 V AC<br>7.5 kA 75 % conforming to EN/IEC 60947-2 - 415 V AC<br>15 kA 75 % conforming to EN/IEC 60947-2 - 240 V AC<br>4.5 kA 75 % conforming to GB 14048.2 - 440 V AC<br>7.5 kA 75 % conforming to GB 14048.2 - 415 V AC<br>15 kA 75 % conforming to GB 14048.2 - 240 V AC |
| [Ui] rated insulation voltage          | 500 V AC conforming to EN/IEC 60947-2                                                                                                                                                                                                                                                                                    |
| [Uimp] rated impulse withstand voltage | 6 kV conforming to EN/IEC 60947-2                                                                                                                                                                                                                                                                                        |
| Contact position indicator             | Yes                                                                                                                                                                                                                                                                                                                      |
| Control type                           | Toggle                                                                                                                                                                                                                                                                                                                   |
| Local signalling                       | ON/OFF indication                                                                                                                                                                                                                                                                                                        |
| Mounting mode                          | Clip-on                                                                                                                                                                                                                                                                                                                  |
| Mounting support                       | DIN rail                                                                                                                                                                                                                                                                                                                 |
| 9 mm pitches                           | 6                                                                                                                                                                                                                                                                                                                        |
| Height                                 | 103 mm                                                                                                                                                                                                                                                                                                                   |
| Width                                  | 54 mm                                                                                                                                                                                                                                                                                                                    |
| Depth                                  | 72 mm                                                                                                                                                                                                                                                                                                                    |
| Colour                                 | Grey                                                                                                                                                                                                                                                                                                                     |
| Mechanical durability                  | 20000 cycles                                                                                                                                                                                                                                                                                                             |
| Electrical durability                  | 10000 cycles                                                                                                                                                                                                                                                                                                             |
| Provision for padlocking               | Padlockable                                                                                                                                                                                                                                                                                                              |
| Connections - terminals                | Tunnel type terminal (top or bottom) 1...25 mm <sup>2</sup> (AWG 18...AWG 8) - rigid<br>Tunnel type terminal (top or bottom) 1...16 mm <sup>2</sup> (AWG 18...AWG 8) - flexible with ferrule<br>Tunnel type terminal (top or bottom) 1...16 mm <sup>2</sup> (AWG 18...AWG 8) - flexible                                  |
| Wire stripping length                  | 14 mm for top or bottom connection                                                                                                                                                                                                                                                                                       |
| Tightening torque                      | 2.5 N.m top or bottom                                                                                                                                                                                                                                                                                                    |
| Earth-leakage protection               | Without                                                                                                                                                                                                                                                                                                                  |

## Environment

|                                       |                                                                                  |
|---------------------------------------|----------------------------------------------------------------------------------|
| IP degree of protection               | IP20 conforming to IEC 60529<br>IP40 (modular enclosure) conforming to IEC 60529 |
| Pollution degree                      | 3 conforming to EN/IEC 60947-2                                                   |
| Tropicalisation                       | 2 conforming to IEC 60068-1                                                      |
| Relative humidity                     | 95 % at 55 °C                                                                    |
| Operating altitude                    | 0...2000 m                                                                       |
| Ambient air temperature for operation | -30...70 °C                                                                      |
| Ambient air temperature for storage   | -40...80 °C                                                                      |

## Offer Sustainability

|                            |                                                                                                                             |
|----------------------------|-----------------------------------------------------------------------------------------------------------------------------|
| Sustainable offer status   | Green Premium product                                                                                                       |
| EU RoHS Directive          | Compliant<br><a href="#">EU RoHS Declaration</a>                                                                            |
| Mercury free               | Yes                                                                                                                         |
| RoHS exemption information | <a href="#">Yes</a>                                                                                                         |
| China RoHS Regulation      | <a href="#">China RoHS declaration</a><br>Product out of China RoHS scope. Substance declaration for your information       |
| Environmental Disclosure   | <a href="#">Product Environmental Profile</a>                                                                               |
| Circularity Profile        | No need of specific recycling operations                                                                                    |
| WEEE                       | The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins |

Contractual warranty

|          |           |
|----------|-----------|
| Warranty | 18 months |
|----------|-----------|