


MGS204



Full-metal magnetic sensor

MGK3070-BPKG/AM/G/US



Application

Pressure rating [bar] 100

Electrical data

Operating voltage [V] 10...30 DC

Current consumption [mA] < 10

Protection class III

Reverse polarity protection yes

Outputs

Electrical design PNP

Output function normally open

Max. voltage drop switching output DC [V] 2.5

Permanent current rating of switching output DC [mA] 200

Switching frequency DC [Hz] 5000

Short-circuit protection yes

Overload protection yes

Detection zone

Sensing range [mm] 70; (referred to magnet M 4.0)

Response sensitivity [mT] 0.9

Accuracy / deviations

Hysteresis [% of Sr] 1...10

Operating conditions

Ambient temperature [°C] -25...75

Protection IP 65; IP 67

MGS204



Full-metal magnetic sensor

MGK3070-BPKG/AM/G/US

Tests / approvals		
EMC	EN 61000-4-2 ESD	4 kV CD / 8 kV AD
	EN 61000-4-3 HF radiated	10 V/m
	EN 61000-4-4 Burst	2 kV
	EN 61000-4-5 Surge	0,5 kV line to line, Ri: 2 Ohm
	EN 61000-4-6 HF conducted	10 V
	EN 55011 emission	class B
	DIN ISO 11452-2	100 V/m
MTTF	[years]	1370
Mechanical data		
Weight	[g]	50.4
Housing		threaded type
Dimensions	[mm]	M18 x 1 / L = 60
Thread designation		M18 x 1
Materials		housing: stainless steel (1.4404 / 316L); sensing face: stainless steel (1.4404 / 316L); plug: PA; lock nuts: brass
Full-metal housing		yes
Displays / operating elements		
Display	switching status	1 x LED, yellow
Accessories		
Accessories (supplied)		lock nuts: 2
Remarks		
Pack quantity		1 pcs.
Electrical connection - plug		
Connector: 1 x M12; Contacts: gold-plated		
		

MGS204

Full-metal magnetic sensor

MGK3070-BPKG/AM/G/US



Connection

