Product datasheet Characteristics

MH30701P01F2200

servo motor MH3 070 1,4Nm,no key,single,no brake,IP65/IP67,6kRPM





Main

		i de la companya de
Range compatibility	PacDrive 3	
Product or component type	AC servo motors	<u> </u>
Device short name	MH3	

Complementary

Maximum mechanical speed	8000 rpm	o
[Us] rated supply voltage	115480 V	
Network number of phases	Three phase	ou: Tit
Continuous stall current	1.78 A	and
Continuous stall torque	1.4 N.m, 115480 V, three phase	
Continuous power	930 W	o.
Peak stall torque	4.2 N.m, 115480 V, three phase	ed t
Nominal output power	0.18 W, 115 V 0.42 W, 230 V 0.75 W, 400 V 0.93 W, 480 V	substitute for and is not to be used for determining suitability
Nominal torque	1.38 N.m, 115 V 1.34 N.m, 230 V 1.3 N.m, 400 V 1.27 N.m, 480 V	a substitute for
Nominal speed	1250 rpm, 115 V 3000 rpm, 230 V 5500 rpm, 400 V 7000 rpm, 480 V	isclaimer: This documentation is not intended as:
Maximum current Irms	5.97 A	
Shaft end	Smooth shaft	ntat
Second shaft	Without second shaft end	
Shaft diameter	11 mm	
Shaft length	23 mm	<u>-</u> ت
IP degree of protection	IP65 standard	Ga.

Encoder type	Single turn SinCos Hiperface
Speed feedback resolution	128 periods
Holding brake	With
Holding torque	3 N.m
Mounting support	International standard flange
Motor flange size	70 mm
Electrical connection	Rotatable right-angled connectors
Torque constant	0.79 N.m/A at 120 °C
Back emf constant	50.72 V/krpm
Number of motor poles	10
Rotor inertia	0.7 kg.cm ²
Stator resistance	8.28 Ohm
Stator inductance	23.4 mH
Stator electrical time constant	2.8 ms
Maximum radial force Fr	660 N at 1000 rpm 520 N at 2000 rpm 460 N at 3000 rpm 410 N at 4000 rpm 380 N at 5000 rpm 360 N at 6000 rpm
Brake pull-in power	7 W
Type of cooling	Natural convection
Length	161 mm
Centring collar diameter	60 mm
Centring collar depth	2.5 mm
Number of mounting holes	4
Mounting holes diameter	5.5 mm
Circle diameter of the mounting holes	82 mm
Product weight	2.6 kg

Offer Sustainability

Green Premium product Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration	
Yes	
China RoHS declaration	
Product Environmental Profile	
No need of specific recycling operations	
The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins	

Contractual warranty

Warranty	18 months