Product datasheet Characteristics

MH30701P12A2200

servo motor MH3 070 1,4Nm,key,multi,no brake,IP65/IP67,6kRPM





Main

	ii ii
PacDrive 3	s or
AC servo motors	
MH3	98
	AC servo motors

Complementary

		a a
Maximum mechanical speed	8000 rpm	
[Us] rated supply voltage	115480 V	
Network number of phases	Three phase	suitability
Continuous stall current	1.78 A	
Continuous stall torque	1.4 N.m, 115480 V, three phase	sed for determining
Continuous power	930 W	
Peak stall torque	4.2 N.m, 115480 V, three phase	Sed 1
Nominal output power	0.18 W, 115 V 0.42 W, 230 V 0.75 W, 400 V 0.93 W, 480 V	and is not to be
Nominal torque	1.38 N.m, 115 V 1.34 N.m, 230 V 1.3 N.m, 400 V 1.27 N.m, 480 V	a substitute for a
Nominal speed	1250 rpm, 115 V 3000 rpm, 230 V 5500 rpm, 400 V 7000 rpm, 480 V	sciaimer: This documentation is not intended as.
Maximum current Irms	5.97 A	isi uc
Shaft end	Parallel key	
Second shaft	Without second shaft end	
Shaft diameter	11 mm	
Shaft length	23 mm	e::
Key width	4 mm	Clair Easi
		<u> </u>

IP degree of protection	IP65 standard
Encoder type	Multiturn SinCos Hiperface
Speed feedback resolution	128 periods
Holding brake	Without
Mounting support	International standard flange
Motor flange size	70 mm
Electrical connection	Rotatable right-angled connectors
Torque constant	0.79 N.m/A at 120 °C
Back emf constant	50.72 V/krpm
Number of motor poles	10
Rotor inertia	0.59 kg.cm²
Stator resistance	8.28 Ohm
Stator inductance	23.4 mH
Stator electrical time constant	2.8 ms
Maximum radial force Fr	660 N at 1000 rpm 520 N at 2000 rpm 460 N at 3000 rpm 410 N at 4000 rpm 380 N at 5000 rpm 360 N at 6000 rpm
Type of cooling	Natural convection
Length	122 mm
Centring collar diameter	60 mm
Centring collar depth	2.5 mm
Number of mounting holes	4
Mounting holes diameter	5.5 mm
Circle diameter of the mounting holes	82 mm
Product weight	1.6 kg

Offer Sustainability

Sustainable offer status	Green Premium product
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS declaration
Environmental Disclosure	Product Environmental Profile
Circularity Profile	No need of specific recycling operations
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

Contractual warranty

	
Warranty	18 months