



Main

Range compatibility	PacDrive 3
Product or component type	AC servo motors
Device short name	MH3

Complementary

Maximum mechanical speed	8000 rpm
[Us] rated supply voltage	115...480 V
Network number of phases	Three phase
Continuous stall current	1.78 A
Continuous stall torque	1.4 N.m, 115...480 V, three phase
Continuous power	930 W
Peak stall torque	4.2 N.m, 115...480 V, three phase
Nominal output power	0.18 W, 115 V 0.42 W, 230 V 0.75 W, 400 V 0.93 W, 480 V
Nominal torque	1.38 N.m, 115 V 1.34 N.m, 230 V 1.3 N.m, 400 V 1.27 N.m, 480 V
Nominal speed	1250 rpm, 115 V 3000 rpm, 230 V 5500 rpm, 400 V 7000 rpm, 480 V
Maximum current Irms	5.97 A
Shaft end	Parallel key
Second shaft	Without second shaft end
Shaft diameter	11 mm
Shaft length	23 mm
Key width	4 mm

IP degree of protection	IP65 standard
Encoder type	Multiturn SinCos Hiperface
Speed feedback resolution	16 periods
Holding brake	Without
Mounting support	International standard flange
Motor flange size	70 mm
Electrical connection	Rotatable right-angled connectors
Torque constant	0.79 N.m/A at 120 °C
Back emf constant	50.72 V/krpm
Number of motor poles	10
Rotor inertia	0.59 kg.cm ²
Stator resistance	8.28 Ohm
Stator inductance	23.4 mH
Stator electrical time constant	2.8 ms
Maximum radial force Fr	660 N at 1000 rpm 520 N at 2000 rpm 460 N at 3000 rpm 410 N at 4000 rpm 380 N at 5000 rpm 360 N at 6000 rpm
Type of cooling	Natural convection
Length	122 mm
Centring collar diameter	60 mm
Centring collar depth	2.5 mm
Number of mounting holes	4
Mounting holes diameter	5.5 mm
Circle diameter of the mounting holes	82 mm
Product weight	1.6 kg

Offer Sustainability

Sustainable offer status	Green Premium product
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS declaration
Environmental Disclosure	Product Environmental Profile
Circularity Profile	No need of specific recycling operations
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

Contractual warranty

Warranty	18 months
----------	-----------