# Product datasheet Characteristics

# MH31003P11F2200

servo motor MH3 100 8Nm,key,single,brake,IP65/IP67,4kRPM





#### Main

		i de la companya de
Range compatibility	PacDrive 3	
Product or component type	AC servo motors	<u> </u>
Device short name	MH3	

#### Complementary

Maximum mechanical speed	6000 rpm	
[Us] rated supply voltage	115480 V	
Network number of phases	Three phase	
Continuous stall current	7.69 A	
Continuous stall torque	9 N.m, 115480 V, three phase	
Continuous power	3270 W	
Peak stall torque	27 N.m, 115480 V, three phase	used for determining suitability
Nominal output power	0.88 W, 115 V 2 W, 230 V 2.85 W, 400 V 3.27 W, 480 V	substitute for and is not to be u
Nominal torque	8.45 N.m, 115 V 7.63 N.m, 230 V 6.8 N.m, 400 V 6.25 N.m, 480 V	a substitute for e
Nominal speed	2500 rpm, 230 V 1000 rpm, 115 V 4000 rpm, 400 V 5000 rpm, 480 V	sclainer: This documentation is not intended as
Maximum current Irms	26.71 A	
Shaft end	Parallel key	
Second shaft	Without second shaft end	
Shaft diameter	19 mm	
Shaft length	40 mm	.e. :
Key width	6 mm	<u>aa</u>

IP degree of protection	IP65 standard
Encoder type	Single turn SinCos Hiperface
Speed feedback resolution	128 periods
Holding brake	With
Holding torque	9 N.m
Mounting support	International standard flange
Motor flange size	100 mm
Electrical connection	Rotatable right-angled connectors
Torque constant	1.17 N.m/A at 120 °C
Back emf constant	77.95 V/krpm
Number of motor poles	10
Rotor inertia	10.3 kg.cm²
Stator resistance	1.08 Ohm
Stator inductance	5.23 mH
Stator electrical time constant	6.3 ms
Maximum radial force Fr	1050 N at 1000 rpm 830 N at 2000 rpm 730 N at 3000 rpm 660 N at 4000 rpm 610 N at 5000 rpm
Brake pull-in power	18 W
Type of cooling	Natural convection
Length	234.3 mm
Centring collar diameter	95 mm
Centring collar depth	3.5 mm
Number of mounting holes	4
Mounting holes diameter	9 mm
Circle diameter of the mounting holes	115 mm
Product weight	8.15 kg

## Offer Sustainability

Sustainable offer status	Green Premium product	
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration	
Mercury free	Yes	
RoHS exemption information	Yes	
China RoHS Regulation	China RoHS declaration	
Environmental Disclosure	Product Environmental Profile	
Circularity Profile	No need of specific recycling operations	
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins	

## Contractual warranty

147	40
Warranty	18 months
	To monate