Product datasheet Characteristics

MH31403P06F2200

servo motor MH3 140 27,8Nm,no key,single 16 lines,brake,IP65/IP67,3kRPM





Main

| | | ā |
|---------------------------|-----------------|---|
| Range compatibility | PacDrive 3 | |
| Product or component type | AC servo motors | |
| Device short name | MH3 | |

Complementary

| Maximum mechanical speed | 4000 rpm | | |
|---------------------------|---|--|--|
| [Us] rated supply voltage | 115480 V | | |
| Network number of phases | Three phase | used for determining suitability | |
| Continuous stall current | 18 A | | |
| Continuous stall torque | 24 N.m, 115480 V, three phase | | |
| Continuous power | 4750 W | | |
| Peak stall torque | 75 N.m, 115480 V, three phase | | |
| Nominal output power | 1.78 W, 115 V 3.55 W, 230 V 4.75 W, 400 V 4.75 W, 480 V | and is not to be | |
| Nominal torque | 22.17 N.m, 115 V 19.3 N.m, 230 V 13.06 N.m, 400 V 13.06 N.m, 480 V | a substitute for e | |
| Nominal speed | 3500 rpm, 400 V 3500 rpm, 480 V 750 rpm, 115 V 1750 rpm, 230 V | scialmer: This documentation is not intended as: | |
| Maximum current Irms | 62.32 A | | |
| Shaft end | Smooth shaft | | |
| Second shaft | Without second shaft end | | |
| Shaft diameter | 24 mm | | |
| Shaft length | 50 mm | <u> </u> | |
| IP degree of protection | IP65 standard | ola iii | |
| | | | |

| Encoder type | Single turn SinCos Hiperface |
|---------------------------------------|--|
| Speed feedback resolution | 16 periods |
| Holding brake | With |
| Holding torque | 23 N.m |
| Mounting support | International standard flange |
| Motor flange size | 140 mm |
| Electrical connection | Rotatable right-angled connectors |
| Torque constant | 1.33 N.m/A at 120 °C |
| Back emf constant | 85.9 V/krpm |
| Number of motor poles | 10 |
| Rotor inertia | 50.27 kg.cm ² |
| Stator resistance | 0.22 Ohm |
| Stator inductance | 3 mH |
| Stator electrical time constant | 13.6 ms |
| Maximum radial force Fr | 2420 N at 1000 rpm 1920 N at 2000 rpm |
| | 1670 N at 3000 rpm |
| Brake pull-in power | 19 W |
| Type of cooling | Natural convection |
| Length | 267 mm |
| Centring collar diameter | 130 mm |
| Centring collar depth | 3.5 mm |
| Number of mounting holes | 4 |
| Mounting holes diameter | 11 mm |
| Circle diameter of the mounting holes | 165 mm |
| Product weight | 18.5 kg |

Offer Sustainability

| Sustainable offer status | Green Premium product | |
|----------------------------|---|--|
| EU RoHS Directive | Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration | |
| Mercury free | Yes | |
| RoHS exemption information | Yes | |
| China RoHS Regulation | China RoHS declaration | |
| Environmental Disclosure | Product Environmental Profile | |
| Circularity Profile | No need of specific recycling operations | |
| WEEE | The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins | |

Contractual warranty

| Warranty | 18 months | |
|----------|-----------|--|