Product datasheet Characteristics

MH31403P16F2200

servo motor MH3 140 27,8Nm,key, single 16 lines,brake,IP65/IP67,3kRPM





Main

		i de la companya de
Range compatibility	PacDrive 3	
Product or component type	AC servo motors	<u> </u>
Device short name	MH3	

Complementary Maximum mechanic

Maximum mechanical speed	4000 rpm	
[Us] rated supply voltage	115480 V	
Network number of phases	Three phase	
Continuous stall current	18 A	
Continuous stall torque	24 N.m, 115480 V, three phase	ie
Continuous power	4750 W	——————————————————————————————————————
Peak stall torque	75 N.m, 115480 V, three phase	used for determining suitability
Nominal output power	1.78 W, 115 V 3.55 W, 230 V 4.75 W, 400 V 4.75 W, 480 V	substitute for and is not to be.
Nominal torque	22.17 N.m, 115 V 19.3 N.m, 230 V 13.06 N.m, 400 V 13.06 N.m, 480 V	a substitute for
Nominal speed	3500 rpm, 400 V 3500 rpm, 480 V 750 rpm, 115 V 1750 rpm, 230 V	This documentation is not intended as
Maximum current Irms	62.32 A	
Shaft end	Parallel key	nntatri
Second shaft	Without second shaft end	
Shaft diameter	24 mm	
Shaft length	50 mm	<u></u>
Key width	8 mm	

IP degree of protection	IP65 standard
Encoder type	Single turn SinCos Hiperface
Speed feedback resolution	16 periods
Holding brake	With
Holding torque	23 N.m
Mounting support	International standard flange
Motor flange size	140 mm
Electrical connection	Rotatable right-angled connectors
Torque constant	1.33 N.m/A at 120 °C
Back emf constant	85.9 V/krpm
Number of motor poles	10
Rotor inertia	50.27 kg.cm ²
Stator resistance	0.22 Ohm
Stator inductance	3 mH
Stator electrical time constant	13.6 ms
Maximum radial force Fr	2420 N at 1000 rpm 1920 N at 2000 rpm 1670 N at 3000 rpm
Brake pull-in power	19 W
Type of cooling	Natural convection
Length	267 mm
Centring collar diameter	130 mm
Centring collar depth	3.5 mm
Number of mounting holes	4
Mounting holes diameter	11 mm
Circle diameter of the mounting holes	165 mm
Product weight	18.5 kg

Offer Sustainability

Sustainable offer status	Green Premium product	
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration	
Mercury free	Yes	
RoHS exemption information	Yes	
China RoHS Regulation	China RoHS declaration	
Environmental Disclosure	Product Environmental Profile	
Circularity Profile	No need of specific recycling operations	
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins	

Contractual warranty

Warranty	18 months
-	