



Main

Range compatibility	PacDrive 3
Product or component type	AC servo motors
Device short name	MH3

Complementary

Maximum mechanical speed	3800 rpm
[Us] rated supply voltage	115...480 V
Network number of phases	Three phase
Continuous stall current	36.1 A
Continuous stall torque	65 N.m, 115...480 V, three phase
Continuous power	9560 W
Peak stall torque	330 N.m, 115...480 V, three phase
Nominal output power	7.75 W, 400 V 7.75 W, 480 V
Nominal torque	37 N.m, 400 V 37 N.m, 480 V
Nominal speed	2000 rpm, 400 V 2000 rpm, 480 V
Maximum current Irms	124.5 A
Shaft end	Smooth shaft
Second shaft	Without second shaft end
Shaft diameter	38 mm
Shaft length	80 mm
IP degree of protection	IP65 standard
Encoder type	Multiturn SinCos Hiperface
Speed feedback resolution	128 periods
Holding brake	With
Holding torque	60 N.m

Mounting support	International standard flange
Motor flange size	190 mm
Electrical connection	Rotatable right-angled connectors
Torque constant	1.8 N.m/A at 120 °C
Back emf constant	129.2 V/krpm
Number of motor poles	10
Rotor inertia	208.8 kg.cm ²
Stator resistance	0.13 Ohm
Stator inductance	3.62 mH
Stator electrical time constant	21.6 ms
Maximum radial force Fr	3300 N at 1000 rpm 3250 N at 2000 rpm 3150 N at 3000 rpm 3100 N at 4000 rpm
Brake pull-in power	25 W
Type of cooling	Natural convection
Length	368 mm
Centring collar diameter	180 mm
Centring collar depth	4 mm
Number of mounting holes	4
Mounting holes diameter	14 mm
Circle diameter of the mounting holes	215 mm
Product weight	71.9 kg

Offer Sustainability

Sustainable offer status	Green Premium product
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS declaration
Environmental Disclosure	Product Environmental Profile
Circularity Profile	No need of specific recycling operations
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

Contractual warranty

Warranty	18 months
----------	-----------