

PRODUCT-DETAILS

MLP125-0-BG

SHRINK-KON 300M BLACK



General Information

Extended Product Type	MLP125-0-BG
Product ID	7TCA017300R0423
EAN	5414363104810
Catalog Description	SHRINK-KON 300M BLACK
Long Description	Heat Shrink Tubing, Flexible for High Specifications, UL/CSA Listed, Thin Wall, Shrink Ratio 2:1, 1/8 Inch/3.2mm Expanded Diameter, Black, 300M, CrossLinked Polyolefin, Item is Silicone, Cadmium and Lead Free

Ordering

EAN	5414363104810
-----	---------------

Dimensions

Product Net Weight	3.54 lb
	1.605 kg

Container Information

Package Level 2 Units	1 reel
Package Level 2 Width	15.4 in
	391 mm
Package Level 2 Height	2.6 in

	66 mm
Package Level 2 Depth /	15.4 in
Length	391 mm

Additional Information

Brand / Label	Shrink-Kon
Color	Black
Flammability Hazard Rating	Flame Retardant
Number of Batteries	0
Process Temperature Rating	-67 to +212 °F -55 to +100 °C
Product Name	PLASTIC CONDUIT
Product Type	Thin-Wall Heat Shrinkable Tubing
Shrink Ratio	2:1
Shrink Temperature	194 °F 90 °C
Thickness	Thin
UPC	786210615318

Certificates and Declarations (Document Number)

Data Sheet, Technical Information	MLP125-0-BG
Instructions and Manuals	MLP125-0-BG

Classifications

ETIM 6	EC000217 - Shrink tubing
ETIM 7	EC000217 - Shrink tubing
UNSPSC	39121723
WEEE Category	Product Not in WEEE Scope
IDEA Granular Category Code (IGCC)	5073 >> Heat shrinkable tube

Categories

Low Voltage Products and Systems → Installation Products → Wire Management and Connectivity → Identification & Heat Shrink

