



PRODUCT-DETAILS

MLP63-0-A

HTSHK 2:1 BLK 1/16IN EXPDIA 1.22M



General Information

Extended Product Type	MLP63-0-A
Product ID	7TCA017310R0314
EAN	5414363105466
Catalog Description	HTSHK 2:1 BLK 1/16IN EXPDIA 1.22M
Long Description	Heat Shrink Tubing, Flexible for High Specifications, UL/CSA Listed, Thin Wall, Shrink Ratio 2:1, 1/16 Inch/1.6mm Expanded Diameter, Black, 25 X 1.22M Lengths, CrossLinked Polyolefin, Item is Silicone, Cadmium and Lead Free

Ordering

EAN	5414363105466
-----	---------------

Dimensions

Product Net Weight	.022 lb
	9.977 g

Container Information

Package Level 2 Units	25 piece
Package Level 2 Width	1.9 in
	48 mm
Package Level 2 Height	1.8 in

	46 mm
Package Level 2 Depth /	49.3 in
Length	1252 mm

Additional Information

Brand / Label	Shrink-Kon
Color	Black
Flammability Hazard Rating	Flame Retardant
Number of Batteries	0
Process Temperature Rating	-67 to +212 °F -55 to +100 °C
Product Name	PLASTIC HEAT SHRINK TUBING
Product Type	Thin-Wall Heat Shrinkable Tubing
Shrink Ratio	2:1
Shrink Temperature	194 °F 90 °C
Thickness	Thin
UPC	786210809052

Certificates and Declarations (Document Number)

Data Sheet, Technical Information	MLP63-0-A
Instructions and Manuals	MLP63-0-A

Classifications

ETIM 6	EC000217 - Shrink tubing
ETIM 7	EC000217 - Shrink tubing
UNSPSC	39121723
WEEE Category	Product Not in WEEE Scope
IDEA Granular Category Code (IGCC)	5073 >> Heat shrinkable tube

Categories

Low Voltage Products and Systems → Installation Products → Wire Management and Connectivity → Identification & Heat Shrink

