




Through-beam sensor receiver

O6E-FNKG/5M



- 1 output function switch
- 2 potentiometer sensitivity
- 3 Light incidence



Application

Function principle

Through-beam sensor

Application

suited for use in the machine tool industry

Electrical data

Operating voltage	[V]	10...30 DC
Current consumption	[mA]	7; ((24 V))
Protection class		III
Reverse polarity protection		yes
Type of light		red light
Wave length	[nm]	633

Outputs

Electrical design		NPN
Output function		light-on/dark-on mode; (selectable)
Max. voltage drop switching output DC	[V]	2.5
Permanent current rating of switching output DC	[mA]	100
Switching frequency DC	[Hz]	1000
Short-circuit protection		yes
Type of short-circuit protection		pulsed

Detection zone

Transmitter / receiver		receiver
Range	[m]	< 10
Range adjustable		yes

O6E403




Through-beam sensor receiver

O6E-FNKG/5M

Operating conditions		
Ambient temperature	[°C]	-25...60
Protection		IP 65; IP 67; IP 68
Tests / approvals		
EMC		EN 60947-5-2
MTTF	[years]	954
UL approval	UL Approval no.	E018
Mechanical data		
Weight	[g]	141.2
Housing		rectangular
Dimensions	[mm]	34.8 x 13 x 21
Materials		housing: stainless steel (1.4404 / 316L); plastics: PPSU; Sealing: FKM
Lens material		PMMA
Lens alignment		side lens
Displays / operating elements		
Display	switching status	1 x LED, yellow
	operation	1 x LED, green
Remarks		
Remarks		operating voltage "supply class 2" according to cULus
Pack quantity		1 pcs.
Electrical connection		
Cable: 5 m, PUR; 3 x 0.25 mm²		

Connection



Core colours :


BN =	brown
BK =	black
BU =	blue

Through-beam sensor receiver

O6E-FNKG/5M

Diagrams and graphs

excess gain graph



x: Abstand [mm]

y: Funktionsreservefaktor