


OGT300



Diffuse reflection sensor

OGT-FPKG/US100



1 programming buttons



Application		
Function principle		Diffuse reflection sensor
Electrical data		
Operating voltage	[V]	10...36 DC
Current consumption	[mA]	25
Protection class		II
Reverse polarity protection		yes
Type of light		red light
Outputs		
Electrical design		PNP
Output function		light-on/dark-on mode; (programmable)
Max. voltage drop switching output DC	[V]	2.5
Permanent current rating of switching output DC	[mA]	150; (200 (...60 °C))
Switching frequency DC	[Hz]	2000
Short-circuit protection		yes
Type of short-circuit protection		pulsed
Overload protection		yes
Detection zone		
Range	[mm]	2...800; (white paper 200 x 200 mm 90 % remission)
Factory setting		\$Hellschaltung
Range adjustable		yes
Max. light spot diameter	[mm]	66
Light spot dimensions refer to		at maximum range
Monitoring range final value	[mm]	150...800
Operating conditions		
Ambient temperature	[°C]	-25...80
Protection		IP 65; IP 67; IP 68; IP 69K



Diffuse reflection sensor

OGT-FPKG/US100


Tests / approvals		
EMC	EN 60947-5-2	
MTTF	[years]	473
Mechanical data		
Weight	[g]	63.4
Housing	threaded type	
Dimensions	[mm]	M18 x 1 / L = 72
Thread designation	M18 x 1	
Materials	stainless steel (1.4404 / 316L); PA; LCP; EPDM; TPU	
Lens material	PMMA	
Displays / operating elements		
Display	switching status	1 x LED, yellow
Teach function	yes	
Electronic lock	yes	
Accessories		
Accessories (supplied)	lock nuts: 2 x	
Remarks		
Remarks	operating voltage "supply class 2" according to cULus	
Pack quantity	1 pcs.	

Electrical connection

Connector: 1 x M12



Connection





Diffuse reflection sensor

OGT-FPKG/US100

Diagrams and graphs

excess gain graph

