


OPU211

Optical fork sensor

OPU-FNKG/AS



- 1 potentiometer sensitivity
- 2 output function switch




Electrical data

Operating voltage [V]	10...35 DC
Current consumption [mA]	< 30
Protection class	III
Reverse polarity protection	yes
Type of light	red light
Wave length [nm]	660



Optical fork sensor

OPU-FNKG/AS

Outputs		
Electrical design	NPN	
Output function	light-on/dark-on mode; (selectable)	
Max. voltage drop switching output DC [V]	2.8	
Permanent current rating of switching output DC [mA]	200	
Switching frequency DC [Hz]	2000	
Short-circuit protection	yes	
Type of short-circuit protection	pulsed	
Overload protection	yes	
Detection zone		
Diameter of the smallest detectable object [mm]	0.8	
Operating conditions		
Ambient temperature [°C]	-25...60	
Protection	IP 67	
Tests / approvals		
EMC	EN 60947-5-2	
MTTF [years]	556	
Mechanical data		
Weight [g]	267.4	
Dimensions [mm]	144 x 12 x 90	
Fork depth D [mm]	60	
Fork width W [mm]	120	
Materials	housing: diecast zinc black anodised; lens: glass	
Displays / operating elements		
Display	switching status	1 x LED, yellow
Remarks		
Pack quantity	1 pcs.	
Electrical connection		
Connector: 1 x M8		
		

OPU211

Optical fork sensor

OPU-FNKG/AS



Connection

