




Through-beam sensor transmitter

OUS-00KG



one transmitting diode each in upper and lower lens



Application

Function principle	Through-beam sensor
--------------------	---------------------

Electrical data

Operating voltage	[V]	10...55 DC
Current consumption	[mA]	20; ((24 V))
Protection class		II
Reverse polarity protection		yes
Type of light		infrared light
Wave length	[nm]	880

Outputs

Short-circuit protection	yes
Type of short-circuit protection	pulsed
Overload protection	yes

Detection zone

Transmitter / receiver	transmitter
Range [m]	< 6
Range adjustable	no
Max. light spot diameter [mm]	734
Light spot dimensions refer to	at maximum range

Operating conditions

Ambient temperature	[°C]	-25...80
Protection		IP 67

Tests / approvals

EMC	EN 60947-5-2	
	EN 55011	class B
MTTF	[years]	1801


OU5005



Through-beam sensor transmitter

OUS-00KG

Mechanical data		
Weight	[g]	137.8
Housing		rectangular
Dimensions	[mm]	28 x 16 x 51
Materials		PPO modified
Lens material		glass
Lens alignment		side lens
Displays / operating elements		
Display	operation	1 x LED, yellow
Accessories		
Accessories (supplied)	Angle bracket: 1 x, E20211	
Remarks		
Pack quantity	1 pcs.	
Electrical connection		
Cable: 2 m, PVC; 2 x 0.34 mm²		
Connection		



Core colours :

BN = brown
BU = blue
BK = black