



Diffuse reflection sensor

OUT-HPKG/6M



receiver in upper lens
transmitter in lower lens



Application

Function principle

Diffuse reflection sensor

Electrical data

Operating voltage	[V]	10...55 DC
Current consumption	[mA]	35; ((24 V))
Protection class		II
Reverse polarity protection		yes
Type of light		infrared light
Wave length	[nm]	880

Outputs

Electrical design		PNP
Output function		light-on mode
Max. voltage drop switching output DC	[V]	2.5
Permanent current rating of switching output DC	[mA]	250
Switching frequency DC	[Hz]	160
Short-circuit protection		yes
Type of short-circuit protection		pulsed
Overload protection		yes

Detection zone

Range	[mm]	1...200; (white paper 200 x 200 mm)
Range adjustable		yes
Max. light spot diameter	[mm]	180
Light spot dimensions refer to		at maximum range

Operating conditions


Ambient temperature	[°C]	-25...80
Protection		IP 67



Diffuse reflection sensor

OUT-HPKG/6M

Tests / approvals		
EMC	EN 60947-5-2	
MTTF	[years]	685
Mechanical data		
Weight	[g]	284
Housing		rectangular
Dimensions	[mm]	28 x 16 x 51
Materials		PPO modified
Lens material		glass
Lens alignment		side lens
Displays / operating elements		
Display	switching status	1 x LED, yellow
Accessories		
Accessories (supplied)	Angle bracket: 1 x, E20211	
Remarks		
Pack quantity	1 pcs.	
Electrical connection		
Cable: 6 m, PVC; 3 x 0.34 mm²		
Connection		



BN	brown
BU	blue
BK	black



Diffuse reflection sensor

OUT-HPKG/6M

Diagrams and graphs

excess gain graph

