

PRODUCT-DETAILS

PKG1806-0-D

SHRINK-KON BOX 3:1 2M BLACK



General Information

Extended Product Type	PKG1806-0-D
Product ID	7TCA017300R0525
EAN	5414363127598
Catalog Description	SHRINK-KON BOX 3:1 2M BLACK
Long Description	Flexible for Moist Environments, Heat Shrink Tubing, 19.0mm Expanded Diameter, Black, 2M, Thin Walled, Material - Crosslinked Polyolefin with Adhesive Lining, Item is Silicone, Cadmium and Lead Free

Ordering

E-Number (Finland)	5240621
EAN	5414363127598

Dimensions

Product Net Weight	.511 lb
	231.746 g

Container Information

Package Level 1 Units	1 piece
Package Level 1 Width	2.4 in
	61 mm

Package Level 1 Height	6.7 in 170 mm
Package Level 1 Depth / Length	6.7 in 170 mm
Package Level 2 Units	60 piece
Package Level 2 Width	15.8 in 401 mm
Package Level 2 Height	22.5 in 572 mm
Package Level 2 Depth / Length	20.9 in 531 mm

Additional Information

Brand / Label	Shrink-Kon
Color	Black
Number of Batteries	0
Process Temperature Rating	-67 to +230 °F -55 to +110 °C
Product Name	PLASTIC CONDUIT
Product Type	Thin-Wall Heat Shrinkable Tubing
Shrink Ratio	3:1
Shrink Temperature	203 °F 95 °C
Thickness	Thin
UPC	786210593739

Certificates and Declarations (Document Number)

Data Sheet, Technical Information	PKG1806-0-D
Instructions and Manuals	PKG1806-0-D

Classifications

ETIM 6	EC000217 - Shrink tubing
ETIM 7	EC000217 - Shrink tubing
UNSPSC	39121723
WEEE Category	Product Not in WEEE Scope
IDEA Granular Category Code (IGCC)	5073 >> Heat shrinkable tube

Categories

Low Voltage Products and Systems → Installation Products → Wire Management and Connectivity → Identification & Heat Shrink

