



PRODUCT-DETAILS

PKG2408-0-B

SHRINK-KON 50M BLACK



General Information

Extended Product Type	PKG2408-0-B
Product ID	7TCA017300R0529
EAN	5414363106937
Catalog Description	SHRINK-KON 50M BLACK
Long Description	Flexible for Moist Environments, Heat Shrink Tubing, 24.0mm Expanded Diameter, Black, 50M, Thin Walled, Material - Crosslinked Polyolefin with Adhesive Lining, Item is Silicone, Cadmium and Lead Free

Ordering

EAN	5414363106937
-----	---------------

Dimensions

Product Net Weight	12.3 lb
	5.578 kg

Container Information

Package Level 2 Units	1 reel
Package Level 2 Width	15.4 in
	391 mm
Package Level 2 Height	10.3 in

	262 mm
Package Level 2 Depth /	15.4 in
Length	391 mm

Additional Information

Brand / Label	Shrink-Kon
Color	Black
Number of Batteries	0
Process Temperature	-67 to +230 °F
Rating	-55 to +110 °C
Product Name	PLASTIC CONDUIT
Product Type	Thin-Wall Heat Shrinkable Tubing
Shrink Ratio	3:1
Shrink Temperature	203 °F
	95 °C
Thickness	Thin
UPC	786210560403

Certificates and Declarations (Document Number)

Data Sheet, Technical Information	PKG2408-0-B
Instructions and Manuals	PKG2408-0-B

Classifications

ETIM 6	EC000217 - Shrink tubing
ETIM 7	EC000217 - Shrink tubing
UNSPSC	39121723
WEEE Category	Product Not in WEEE Scope
IDEA Granular Category Code (IGCC)	5073 >> Heat shrinkable tube

Categories

Low Voltage Products and Systems → Installation Products → Wire Management and Connectivity → Identification & Heat Shrink

