

Description Interruttore automatico scatolato

Code MSXE 400

No. of poles 4P

Rated current 400 A

Release Electronic

ELECTRICAL CHARACTERISTICS


Standard	IEC/EN 60947-2	Execution	Fixed - Plug-in
Use category	B	DIN rail mounting	No
Rated frequency (Hz)	50 / 60	Can be equipped with motor operator	Si
Rated operating voltage (Ue)	690 Vac	Compatible interlock	Lever – Cable
Rated impulse withstand voltage (Uimp)	8 kV	Terminals supplied	Front FC
Overvoltage category	IV	Assembly position	Any
Insulation voltage (Ui)	800 V	Upline/downline power supply	Si
Thermal regulation	0,4 - 0,5 - 0,63 - 0,8 - 0,9 - 0,95 - 1 x In	Electrical life (415Vac)	4.500 cycles
Magnetic regulation	Electronic LSIG	Mechanical life	15.000 cycles
Neutral protection	50% - 100% x Ir	Operating temperature	-5°C +65°C
Total power loss	83.2 W	Stocking temperature	-20° +65°
Rated short-circuit current making capacity (Icm)	-	Weight (kg)	5.7
Rated short-time withstand current for 0,3s (Icw)	5 kA	Width	185 mm
I _{dn} regulation	-	Height	260 mm
DT regulation	-	Depth	103 mm

SERVICE BREAKING CAPACITY (ICU)

220/240Vac	50 kA	220/240Vac	50 kA
400/415Vac	36 kA	400/415Vac	36 kA
440Vac	25 kA	440Vac	25 kA
525Vac	15 kA	525Vac	15 kA
690Vac	10 kA	690Vac	10 kA
250Vdc	-	250Vdc	-

RATED BREAKING CAPACITY (ICS)

DIMENSIONAL





Product Data Sheet

GWD9374

MSX

STANDARDS/APPROVALS

