




The distribution board for construction sites type Q-BOX are designed to withstand the effects of wear, impact and the stress caused by atmosph. They come in pre-wired versions fitted with interlocked socket-outlets (with or without a fuse-holder) up to 63A, or socket-outlets type IEC 309. The wired versions are also equipped with accessories like the emergency push-button, lockable doors, stainless steel tear-proof cable-fastening hooks, and built-in transportation handles on the upper part of the board. To ensure the best possible positioning on the construction site, 68 Q-BOX ACS boards can be surface-mounted, floor-mounted or fitted on poles.

Type	Q-BOX 6 ACS		board type	Wired
Colour	Light blue		Outer dim. LxHxD (mm)	914x821x400
Weight (kg)	31		Accordance with Standards	EN 61439-4 (ACS)
Characteristics	UV resistance (EN 62208)		IP degree	IP55
Mechanical resistance	IK10		Glow wire test	650 °C
Thermo-pressure with ball	70 °C		Insulation class	II
Power supply	Terminal block		No. of poles	3P+N+E
Power suppleable (kW)	17		Mains switch	RCBO 32A 4P 6 kA 0,03A - AC type
Circuits protection	Fuse		No. socket outlets	6
Socket-outlet 2P+E 16A - IB	3		Socket-outlet 3P+E 16A - IB	2
Socket-outlet 3P+N+E 16A - IB	1		Emergency push-button	Yes

#### BEHAVIOUR WITH CHEMICAL AND ATMOSPHERIC AGENTS

Saline solution	Acids		Bases		Solvents				Mineral oil	UV rays
	Concentrated	Diluted	Concentrated	Diluted	Hexane	Benzol	Acetone	Ethyl alcohol		
Resistant	Limited resistance	Resistant	Limited resistance	Resistant	Limited resistance	Limited resistance	Limited resistance	Resistant	Limited resistance	Resistant

#### DIMENSIONAL



#### TECHNICAL SYMOLOGY



EN 61439-4 (ACS)



EN 62208

IP


IP55

IK

IK10

GWT

650 °C



70 °C



II

#### STANDARDS/APPROVALS

