



70 RT HP is a complete offer of rotary isolator switches from 16 A to 160 A, available in boxes both in insulating material and aluminium, in control or emergency versions, compatible with the main applications for residential, tertiary and industrial contexts.

DC versions for photovoltaic applications are also available from 16 A to 40 A in insulating box.


The series is completed with versions for board from 16 A to 1000 A and for DIN rail fixing from 16 A to 63 A, which can be equipped with auxiliary contacts.

The devices have been designed to reduce wiring time, facilitate installation and guarantee the maximum safety and robustness even in the most demanding conditions.

ELECTRICAL CHARACTERISTICS

	Rotary isolator	Version	For board
Circuit breaker			
Rated current (A)	63	No. of modules EN 50022	5
No. of poles	3P	Adjustment range	114 - 177 mm
Rated operational current AC-21A (415 V) (A)	63	Type	For emergency
Rated operational current AC-22A (415 V) (A)	63	Knob colour	Red
Rated operational current AC-23A (415 V) (A)	63	Lockable	YES (max. 3 locks in OFF)
Power dissipation per pole	2,58 W/pole	ACCESSORIES	
Cable section	2,5-25 mm ²	Type of accessory	Max. 2 auxiliary contacts (1 per side)

DIMENSIONAL



STANDARDS/APPROVALS

