



70 RT HP is a complete offer of rotary isolator switches from 16 A to 160 A, available in boxes both in insulating material and aluminium, in control or emergency versions, compatible with the main applications for residential, tertiary and industrial contexts.

DC versions for photovoltaic applications are also available from 16 A to 40 A in insulating box.



The series is completed with versions for board from 16 A to 1000 A and for DIN rail fixing from 16 A to 63 A, which can be equipped with auxiliary contacts.

The devices have been designed to reduce wiring time, facilitate installation and guarantee the maximum safety and robustness even in the most demanding conditions.

ELECTRICAL CHARACTERISTICS

ELECTRICAL CHARACTERISTICS		- FUNCTIONAL CHARACTERISTICS		-
Circuit breaker	Rotary isolator	Version		For board
Rated current (A)	250	No. of modules EN 50022		9
No. of poles	3P	Adjustment range		152 - 246 mm
Rated operational current AC-21A (415 V) (A)	250	Type		Control
Rated operational current AC-22A (415 V) (A)	250	Knob colour		Black
Rated operational current AC-23A (415 V) (A)	250	Lockable		YES (max. 3 locks in OFF)
Power dissipation per pole	6,5 W/pole	ACCESSORIES		-
Cable section	70-185 mm²	Type of accessory		Max. 8 auxiliary contacts (4 per side)

DIMENSIONAL



STANDARDS/APPROVALS

