

Product Data Sheet

tel: +38 032 84 81 11 fax: +38 032 84 88 08 S4088 Centre 2010 - Belgamo - Italy GEWISS 2 d.d. Via A. Volpi 1	last update 11/08/2022 es@gewiss.com www.gewiss.com	and could be considered without previous notice only as informative purposes Data, measures, designs and pictures are shown
--	---	---

70 RT HP is a complete offer of rotary isolator switches from 16 A to 160 A, available in boxes both in insulating material and aluminium, in control or emergency versions, compatible with the main applications for residential, tertiary and industrial contexts.

DC versions for photovoltaic applications are also available from 16 A to 40 A in insulating box.

The series is completed with versions for board from 16 A to 1000 A and for DIN rail fixing from 16 A to 63 A, which can be equipped with auxiliary contacts.

The devices have been designed to reduce wiring time, facilitate installation and guarantee the maximum safety and robustness even in the most demanding conditions.

ELECTRICAL CHARACTERISTICS	-	FUNCTIONAL CHARACTERISTICS	-
Circuit breaker	Rotary isolator	Version	Enclosed
Rated current (A)	16	Material	Insulating
No. of poles	3P	Type	Control
Rated insulation voltage Ui (Vac)	690	Knob colour	Black
Rated operational current AC-21A (415 V) (A)	16	Lockable	YES (max. 3 locks in ON and OFF)
Rated operational current AC-22A (415 V) (A)	16	IP degree	IP66/IP67/IP69
Rated operational current AC-23A (415 V) (A)	16	Mechanical resistance	IK08
Conditional short circuit current Icc (415 V) (kA)	10	Protection against indirect contact	Double insulation
Cable section	1-10 mm²	Operating temperature	-25 +60 °C
ACCESSORIES	-	Cable entries on top	2 x M20/M25 knock-outs
Type of accessory	Max. 2 auxiliary contacts (1 per side)	Cable entries on bottom	2 x M20/M25 knock-outs

BEHAVIOUR WITH CHEMICAL AND ATMOSPHERIC AGENTS										
Saline solution	Acids		Bases		Solvents				Mineral oil	UV rays
	Concentrated	Diluted	Concentrated	Diluted	Hexane	Benzol	Acetone	Ethyl alcohol		
Resistant	Limited resistance	Resistant	Not resistant	Limited resistance	Limited resistance	Not resistant	Not resistant	Limited resistance	Resistant	Resistant

DIMENSIONAL

