

Product Data Sheet

tel: +38 032 84 81 11 fax: +38 032 84 88 08 Gewiss Centre 2010 - Bergamo - Italy GEWISS S.p.A. Via A. Volpi 1	last update 11/08/2012 es@gewiss.com www.gewiss.com	and could be changed without previous notice only as informative purposes Data, measures, designs and pictures are shown
---	---	--

German standard wall mounting enclosure equipped with bipolar terminal blocks and two interchangeable flanges (1 flange with knock-out elements and 1 flange with quick entry cable glands).

Insulation class	II	Colour	Grey RAL 7035
Outer dim. LxHxD (mm)	298x420x140	IP degree	IP65
Installation	Wall mounting	Mechanical resistance	IK07
Door colour	Smoked Transparent	Terminal block N (mm²)	(3x25)+(10x10)
Terminal block T (mm²)	(3x25)+(10x10)	No. of modules EN 50022	24 (12X2)
Glow Wire Test	750 °C	Standard	IEC EN 60670-1; IEC EN 60670-24; DIN VDE 0603-1
Operating temperature	-25 +60 °C	Thermo-pressure with ball	70 °C
Pole 1 (mm²)	N (3x35) + (10x10)	Pole 2 (mm²)	E (3x35) + (10x10)

BEHAVIOUR WITH CHEMICAL AND ATMOSPHERIC AGENTS										
Saline solution	Acids		Bases		Solvents				Mineral oil	UV rays
	Concentrated	Diluted	Concentrated	Diluted	Hexane	Benzol	Acetone	Ethyl alcohol		
Resistant	Not resistant	Limited resistance	Limited resistance	Not resistant	Limited resistance	Not resistant	Not resistant	Limited resistance	Limited resistance	Resistant

DIMENSIONAL

