

Product Data Sheet

tel: +38 032 84 81 11 fax: +38 032 84 88 08 S4088 Centre 2010 - Belgamo - Italy GEWISS S.p.A. Via A. Volpi 1	last update 11/08/2022 sa@gewiss.com www.gewiss.com	and could be changed without previous notice only as informative purposes Data, measures, designs and pictures are shown
--	---	--



French standard wall mounting enclosure equipped with multipolar terminal blocks. Walls with knock-out elements.

Insulation class	II	Colour	White RAL 9016
Outer dim. LxHxD (mm)	250x475x93.5	IP degree	IP30
Installation	Wall mounting	Mechanical resistance	IK07
No. of modules EN 50022	39 (13x3)	Glow Wire Test	750 °C
Standard	IEC EN 60670-1; IEC EN 60670-24; NF C 61-910	Operating temperature	-25 +60 °C
Thermo-pressure with ball	70 °C	Phase terminal block (mm²)	L(1x35)+(5x25)
Neutral terminal block (mm²)	N(1x35)+(5x25)	Earth terminal block (mm²)	E(7x25)+(36x4)

BEHAVIOUR WITH CHEMICAL AND ATMOSPHERIC AGENTS										
Saline solution	Acids		Bases		Solvents				Mineral oil	UV rays
	Concentrated	Diluted	Concentrated	Diluted	Hexane	Benzol	Acetone	Ethyl alcohol		
Resistant	Not resistant	Limited resistance	Limited resistance	Not resistant	Limited resistance	Not resistant	Not resistant	Limited resistance	Limited resistance	Resistant

DIMENSIONAL

