




Insulation class	II	Colour	White RAL 9016
Outer dim. LxHxD (mm)	250x600x93.5	IP degree	IP30
Installation	Wall mounting	Mechanical resistance	IK07
No. of modules EN 50022	52 (13x4)	Glow Wire Test	750 °C
Standard	IEC EN 60670-1; IEC EN 60670-24; NF C 61-910	Operating temperature	-25 +60 °C
Thermo-pressure with ball	70 °C	Phase terminal block (mm²)	L(1x35)+(5x25)
Neutral terminal block (mm²)	N(1x35)+(5x25)	Earth terminal block (mm²)	E(8x25)+(48x4)

BEHAVIOUR WITH CHEMICAL AND ATMOSPHERIC AGENTS

Saline solution	Acids		Bases		Solvents				Mineral oil	UV rays
	Concentrated	Diluted	Concentrated	Diluted	Hexane	Benzol	Acetone	Ethyl alcohol		
Resistant	Not resistant	Limited resistance	Limited resistance	Not resistant	Limited resistance	Not resistant	Not resistant	Limited resistance	Limited resistance	Resistant

DIMENSIONAL

TECHNICAL SYMBOLOGY

IP


IP30

IK

IK07

GWT

750 °C



II

STANDARDS/APPROVALS

