




Pressure transmitter

PT-100-SBG14-A-ZVG/US/ IW



- 1 Sealing
Tightening torque 25 Nm



Application

Application	for industrial applications
Media	liquids and gases
Medium temperature [°C]	-25...90
Pressure rating [bar]	200
Min. bursting pressure [bar]	1000
Type of pressure	relative pressure

Electrical data

Operating voltage [V]	8.5...36 DC
Min. insulation resistance [MΩ]	100; (500 V DC)
Protection class	III
Reverse polarity protection	yes

Inputs / outputs

Number of inputs and outputs	Number of analogue outputs: 1
------------------------------	-------------------------------

Outputs

Total number of outputs	1
Output signal	analogue signal
Number of analogue outputs	1
Analogue current output [mA]	4...20
Max. load [Ω]	775; (U _b = 24 V; (U _b - 8,5 V) / 20 mA)

Measuring/setting range

Measuring range [bar]	0...100
-----------------------	---------



Pressure transmitter

PT-100-SBG14-A-ZVG/US/ IW

Accuracy / deviations		
Repeatability	[% of the span]	$< \pm 0,1$; (with temperature fluctuations < 10 K)
Characteristics deviation	[% of the span]	$< \pm 1,0$; (incl. drift when overtightened, zero point and span error)
Linearity deviation	[% of the span]	$< \pm 0,25$ (BFSL) / $< \pm 0,5$ (LS)
Hysteresis deviation	[% of the span]	$< \pm 0,2$
Long-term stability	[% of the span]	$< \pm 0,1$; (per 6 months)
Temperature coefficient zero point	[% of the span / 10 K]	$< \pm 0,1$; (-25...90 °C)
Temperature coefficient span	[% of the span / 10 K]	$< \pm 0,1$; (-25...90 °C)
Response times		
Step response time analogue output	[ms]	3
Operating conditions		
Ambient temperature	[°C]	-25...90
Storage temperature	[°C]	-40...100
Protection		IP 67; IP 69K
Tests / approvals		
EMC	EN 61000-4-2 ESD	4 kV CD / 8 kV AD
	EN 61000-4-3 HF radiated	10 V/m
	EN 61000-4-4 Burst	4 kV coupling clamp
	EN 61000-4-5 Surge	1 kV signal for DC units
	EN 61000-4-6 HF conducted	10 V
Shock resistance	DIN IEC 68-2-27	50 g (11 ms)
Vibration resistance	DIN IEC 68-2-6	20 g (10...2000 Hz)
MTTF	[years]	1579
Mechanical data		
Weight	[g]	79.6
Materials		stainless steel (1.4404 / 316L); PA
Materials (wetted parts)		stainless steel (1.4404 / 316L); Sealing: FKM
Min. pressure cycles		50 million
Process connection		threaded connection G 1/4 external thread
Remarks		
Remarks		BFSL = Best Fit Straight Line LS = limit value setting
Notes		discontinued article
Pack quantity		1 pcs.
Electrical connection		
Connector: 1 x M12		

PT3542

Pressure transmitter

PT-100-SBG14-A-ZVG/US/ /W



Connection

