



Main

Range of product	Zelio Time
Product or component type	Industrial timing relay
Discrete output type	Solid state
Component name	RE9
Time delay type	A
Time delay range	0.1...10 s

Complementary


Width pitch dimension	22.5 mm
[Us] rated supply voltage	24...240 V AC/DC at 50/60 Hz
Voltage range	0.85...1.1 Us
Connections - terminals	Screw terminals, clamping capacity: 2 x 2.5 mm ² flexible without cable end Screw terminals, clamping capacity: 2 x 1.5 mm ² flexible with cable end
Tightening torque	0.6...1.1 N.m
Setting accuracy of time delay	< +/- 20 %
Repeat accuracy	< 1 %
Reset time	>= 100 ms after time delay period
Temperature drift	<= 0.1 %/°C
Continuous output current	<= 0.7 A at 20 °C
Minimum output current	10 mA at 20 °C
Overload current	<= 15 A during 10 ms conforming to VDE 0435 (part 303), 4.8.3/class II
Voltage drop	<= 3 V closed contact(s) 0.7 A
Leakage current	<= 6 mA open contact contact(s)
Power dissipation in W	<= 2.5 W
Electrical durability	> 100000000 cycles
Marking	CE
Overvoltage category	III conforming to IEC 60664-1
[Ui] rated insulation voltage	300 V CSA certified 250 V IEC certified
Supply disconnection value	> 0.1 Uc
Operating position	Any position without derating
Surge withstand	2 kV conforming to IEC 61000-4-5 level 3
CAD overall width	22.5 mm
CAD overall height	78 mm
CAD overall depth	80 mm
Product weight	0.11 kg

Environment


Immunity to microbreaks	<= 2 ms after time delay period <= 100 ms during time delay period
Derating factor	None for > 20 °C
Standards	EN/IEC 61812-1
Product certifications	CSA GL UL
Ambient air temperature for storage	-40...85 °C
Ambient air temperature for operation	-20...60 °C
Relative humidity	15...85 % (3K3) conforming to IEC 60721-3-3
Vibration resistance	0.35 mm (f = 10...55 Hz) conforming to IEC 60068-2-6
Shock resistance	15 gn for 11 ms conforming to IEC 60068-2-27
IP degree of protection	IP50 (housing) IP20 (terminals)
Pollution degree	3 conforming to IEC 60664-1
Dielectric strength	2.5 kV
Non-dissipating shock wave	4.8 kV
Resistance to electrostatic discharge	8 kV (in air) conforming to IEC 61000-4-2 level 3 6 kV (in contact) conforming to IEC 61000-4-2 level 3
Resistance to electromagnetic fields	10 V/m conforming to IEC 61000-4-3 level 3
Resistance to fast transients	2 kV conforming to IEC 61000-4-4 level 3
Disturbance radiated/conducted	CISPR 11 group 1 - class A CISPR 22 - class A

Width 22.5 mm


Rail Mounting



Screw Fixing



Internal Wiring Diagram



Recommended Application Wiring Diagram



The timing relay is placed in series, with the load whose energisation is to be delayed on one side and switch K on the other side. The mains supply may be a.c. or d.c. and the voltage may be between 24 V and 240 V.

Function A : Power on Delay Relay

Description

The timing period T begins on energisation. After timing, the output(s) R close(s). The second output can be either timed or instantaneous.

Function: 1 Output



Function: 2 Outputs



2 timed outputs (R1/R2) or 1 timed output (R1) and 1 instantaneous output (R2 inst.)

Legend

Relay de-energised

Relay energised

Output open

Output closed

C Control contact

G Gate

R Relay or solid state output

R1/ 2 timed outputs

R2

The second output is instantaneous if the right position is selected

inst.

T Timing period

Ta Adjustable On-delay

-

Tr Adjustable Off-delay

-

U Supply