



Main

Range of product	Zelio Control
Product or component type	Industrial measurement and control relays
Relay type	Current measurement relay
Relay name	RM4J
Relay monitored parameters	Overcurrent or undercurrent detection
Time delay	Adjustable 0.05...30 s
Power consumption in VA	2.7...3 VA AC
Measurement range	100...1000 mA current AC 10...100 mA current AC 0.3...30 mA current AC 100...1000 mA current DC 10...100 mA current DC 0.3...30 mA current DC
Contacts type and composition	2 C/O

Complementary

[Us] rated supply voltage	380...415 V AC, 50/60 Hz +/- 5 %
Operating voltage tolerance	0.85...1.1 Un
Output contacts	2 C/O
Measuring cycle	<= 80 ms
Internal input resistance	1 Ohm 10 Ohm 33 Ohm
Permissible continuous overload	0.05 A 0.15 A 1.5 A
Permissible non repetitive overload	0.5 A 0.2 A 5 A
Setting accuracy of the switching threshold	+/- 5 %
Switching threshold drift	<= 0.5 % within the supply voltage range (0.85...1.1 Un) <= 0.06 % per degree centigrade depending permissible ambient air temperature
Setting accuracy of time delay	10 P
Time delay drift	<= 0.5 % within the supply voltage range (0.85...1.1 Un) <= 0.07 % per degree centigrade depending on temperature
Hysteresis	5...30 % adjustable of current threshold setting
Marking	CE : EMC 89/336/EEC CE : LVD 73/23/EEC
Overvoltage category	III conforming to IEC 60664-1
[Ui] rated insulation voltage	500 V conforming to IEC
Supply disconnection value	> 0.1 Un
Operating position	Any position without derating
Connections - terminals	Screw terminals 2 x 2.5 mm ² , flexible cable without cable end Screw terminals 2 x 1.5 mm ² , flexible cable with cable end
Tightening torque	0.6...1.1 N.m
Mechanical durability	30000000 cycles
[Ith] conventional free air thermal current	8 A


[le] rated operational current	0.3 A at 115 V DC-13 70 °C conforming to VDE 0660 0.3 A at 115 V DC-13 70 °C conforming to IEC 60947-5-1/1991 0.1 A at 250 V DC-13 70 °C conforming to VDE 0660 0.1 A at 250 V DC-13 70 °C conforming to IEC 60947-5-1/1991 3 A at 250 V AC-15 70 °C conforming to VDE 0660 3 A at 250 V AC-15 70 °C conforming to IEC 60947-5-1/1991 3 A at 24 V AC-15 70 °C conforming to VDE 0660 3 A at 24 V AC-15 70 °C conforming to IEC 60947-5-1/1991 3 A at 115 V AC-15 70 °C conforming to VDE 0660 3 A at 115 V AC-15 70 °C conforming to IEC 60947-5-1/1991 2 A at 24 V DC-13 70 °C conforming to VDE 0660 2 A at 24 V DC-13 70 °C conforming to IEC 60947-5-1/1991
Switching capacity in mA	10 mA at 12 V
Switching voltage	250 V AC <= 440 V AC
Contacts material	90/10 silver nickel contacts
Number of cables	2
Width	23 mm
Height	78 mm
Depth	80 mm
Terminals description ISO n°1	(15-16-18)OC (25-26-28)OC (A1-A2)CO (C-B1-B2-B3)CO
Output relay state	Tripped if A measured > A set Tripped if V measured > V set
9 mm pitches	2.5
Product weight	0.172 kg

Environment

Standards	EN/IEC 60255-6
Product certifications	CSA GL UL
Ambient air temperature for storage	-40...85 °C
Ambient air temperature for operation	-20...65 °C
Environmental characteristic	3K3
Relative humidity	15...85 % conforming to IEC 60721-3-3
Shock resistance	15 gn for 11 ms conforming to IEC 60255-21-1
IP degree of protection	IP50 (casing) conforming to IEC 60529 IP20 (terminals) conforming to IEC 60529
Pollution degree	3 conforming to IEC 60664-1
Dielectric test voltage	2.5 kV
Non-dissipating shock wave	4.8 kV
Resistance to electrostatic discharge	8 kV air conforming to IEC 61000-4-2 level 3 6 kV contact conforming to IEC 61000-4-2 level 3
Resistance to electromagnetic fields	10 V/m conforming to IEC 61000-4-3 level 3
Resistance to fast transients	2 kV conforming to IEC 61000-4-4 level 3
Protection against electric shocks	2 kV : level 3 conforming to IEC 61000-4-5
Disturbance radiated/conducted	CISPR 11 group 1 - class A CISPR 22 - class A


Current Measurement Relays

Dimensions




Current Measurement Relays

Rail mounting




Screw fixing



Current Measurement Relays

RM4JA01 Wiring Diagram



A1- Supply voltage

A2

B1, Currents to be measured (see table below)


B2,

B3, C

Connection and current values to be measured

B1-C	3...30 mA
B2-C	10...100 mA
B3-C	0.1...1 A

RM4JA31 Wiring Diagram



A1- Supply voltage

A2

B1, Currents to be measured (see table below)


B2,

B3, C

Connection and current values to be measured

B1-C	3...30 mA
B2-C	10...100 mA
B3-C	0.1...1 A

RM4JA32 Wiring Diagram



A1- Supply voltage

A2

B1, Currents to be measured (see table below)

B2,


B3, C

Connection and current values to be measured


B1-C	0.3...1.5 A
B2-C	1...5 A
B3-C	3...15 A

Example: Detection of Blockage on a Crusher (Overcurrent Function)

Current measured ≤ 15 A




Current measured > 15 A



Electrical Durability and Load Limit Curves

AC Load


Curve 1: Electrical durability of contacts on resistive load in millions of operating cycles



X Current broken in A

Y Millions of operating cycles

Curve 2: Reduction factor k for inductive loads (applies to values taken from durability Curve 1)




X Power factor on breaking ($\cos \varphi$)

Y Reduction factor K

DC Load

Load limit curve




X Current in A

Y Voltage in V

1 L/R = 20 ms

2 L/R with load protection diode


3 Resistive load



Function Diagram

Overcurrent Detection

Function “>”




Legend

- t Time delay
- U A1-A2 Supply voltage
- IS1 Setting current threshold
- IS2 Current measured
- 15-18, 15-16; 25-28, 25-26 Output relays connections
- Relay status: black color = energized.

Function Diagram

Undercurrent Detection

Function “<”



Legend

- t Time delay
- U A1-A2 Supply voltage
- IS1 Setting current threshold
- IS2 Current measured
- 15-18, 15-16; 25-28, 25-26 Output relays connections
- Relay status: black color = energized.