

RV6002



Incremental encoder with solid shaft

RV-0060-I24/L2



Status Archive

/RV3500



- 1 reference mark
- 2 M3 Depth 5 mm



Application

Function principle incremental

Electrical data

Operating voltage [V] 10...30 DC
Current consumption [mA] 150

Outputs

Electrical design HTL
Max. current load per output [mA] 50
Switching frequency [kHz] 300
Type of short-circuit protection < 60 s
Phase difference A und B [°] 90

Measuring/setting range

Resolution 60 resolution

Operating conditions

Ambient temperature [°C] -30...85
Storage temperature [°C] -30...100
Max. relative air humidity [%] 98
Protection IP 64

RV6002



Incremental encoder with solid shaft

RV-0060-I24/L2

Tests / approvals		
Shock resistance		100 g (6 ms)
Vibration resistance		10 g (55...2000 Hz)
MTTF	[years]	190
Mechanical data		
Weight	[g]	44
Dimensions	[mm]	Ø 58 / L = 46
Materials		aluminium
Max. revolution, mechanical [U/min]		12000
Max. starting torque	[Nm]	1
Reference temperature torque	[°C]	20
Shaft design		solid shaft
Shaft diameter	[mm]	10
Shaft material		steel (1.4104)
Max. shaft load axial (at the shaft end)	[N]	10
Max. shaft load radial (at the shaft end)	[N]	20
Remarks		
Notes	discontinued article	
Electrical connection		
Cable: 2 m, PUR; axial		
brown	A	
green	A inverted	
grey	B	
pink	B inverted	
red	0 index	
black	0 index inverted	
blue	L+ sensor	
white	0V sensor	
brown/green	L+ (Up)	
white/green	0V (Un)	
lilac	failure inverted	
screen	housing	

RV6002


Incremental encoder with solid shaft

RV-0060-I24/L2



Diagrams and graphs

Pulse diagram



Output A

Output B

0 index

Status Archive

/RV3500