RXZE2M114

socket RXZ - mixed contact -10A - < 250V - screw clamp -for relay RXM2.., RXM4..



Main Range of product Zelio Relay Product or component type Socket Contact terminal arrangement Mixed Product compatibility Plug-in relay RXM (4 C/O) Plug-in relay RXM (2 C/O) Shape of pin Flat Device short name RXZ

10

Complementary

o o mpromornany		
[Ith] conventional free air thermal current	10 A	
[Ue] rated operational voltage	< 250 V	
Tightening torque	<= 1 N.m (M3 screw(s))	
Fixing mode	Clip-on 35 mm symmetrical DIN rail By screw panel	
Marking	CE	
Width	30 mm	
Product weight	0.048 kg	

Sale per indivisible

quantity


Environment

Connections - terminals	Screw clamp terminals, solid cable without cable end 2 x 0.52 x 1.5 mm ² /AWG	
	20AWG 16	
	Screw clamp terminals, solid cable without cable end 1 x 0.51 x 1.5 mm²/AWG 20AWG 16	
	Screw clamp terminals, flexible cable with cable end 2 x 0.252 x 1 mm²/AWG 22AWG 17	
	Screw clamp terminals, flexible cable with cable end 1 x 0.251 x 1 mm 2 /AWG 22AWG 17	
Standards	IEC 61984	
Product certifications	CSA	
	UL	
	Lloyd's	
Ambient air temperature for storage	-4085 °C	
Ambient air temperature for operation	-4055 °C	
IP degree of protection	IP20 conforming to EN/IEC 60529	
Dielectric strength	2500 V	

RXZE2M114

Socket

Socket with Mixed Contact Terminals and Clamp Terminals



- Relay Protection Module Carriage Stirrup
- 2